SignalTight™ Plenum Cable

The universal continuity solution



Protection against loose connectors

Digital services are seriously impacted by loose connectors:

Pixelation and tilting of video

Reduced data speeds

Poor VoiP voice quality

SignalTight™ Drop Connectors minimize the number of self-installs that become truck rolls

Achieves signal transmission approaching that of a fully-tightened connector, even if loose

- Unique 7/16" nut profile allows hand tightening while discouraging wrench-tightening on CPEs
- Knurled grip enhances ability to pre-tighten with fingers prior to wrench tight
- Maintains ground continuity even when very loose
- Reduces QAM errors/packet loss
- Prevents service issues from loose connections





Product Specifications

1 Todact Specifications				
Bandwidth	0 MHz to 3 GHz			
Impedance	75 Ohms (nominal)			
Return Loss	Minimum -30 dB to 3 GHz			
Insertion Loss	Less than .10 dB to 3 GHz			
Shielding Effectiveness* (Dynamic)	Enhanced by 25dB			
Operating Voltage	90 V (at 60 Hz continuous AC)			
Operating Temperature	-40° F to + 140° F (-40° C to 60° C)			
Cable Retention	45 lbs (20.41 kg) minimum			

Meets or Exceeds all SCTE Specifications

EX11N716PLPLUS



Part Numbers

EX11N716PLPLUS

SignalTight™, EX series, universal compression connector, movable push-up pin, 11 series cable, NiTin-plated, Plenum Cable

Preparation & installation loois					
Compression Tool	VT200	VT300	CATAS	CAT-AS-EX	
1/4" – 1/4" universal drop cable preparation tool	DDT59611		UDT596711		
7/16" snap torque wrench	TW207	TW309	TW307 AH		

Dramaration O Installation Table

^{*} As compared to standard connector. Tests were performed with the nut in loose condition with dynamic motion applied to the jumpers