

# LDT Lightweight Drop Trimmer



- Lightweight and compact body design allows cable preparation of 59, 6 and N48 coax cable (std, tri and quad) without adjustment or blade cassette change out
- One step cable preparation precisely exposes the center conductor by 5/16 in. (7.93 mm) and removes the proper length of jacket at 1/4 in. (6.35 mm)
- LDT-MINI, LDT-MINI-125 and LDT-MINI-1 has 1.4 inches (6.35mm) center conductor exposure
- Supplied with unique polymer braid brush attachment for folding back the braid after cable preparation
- Built in strip stop for precise preparation every time
- Lightweight, impact resistant "High-Visibility" yellow polymer construction
- Superior quality tool steel blade cassettes will perform 3500+ preparations under normal use
- Blade cassettes color-coded and marked with cable series type for easy identification
- Length: 4 in. (102 mm)
- Weight: 0.8 oz (23 g)
- Made of Chinese and American parts
- Engineered in the U.S.A
- See tables for part numbers

Model/Part#	Drop Cable Series	Replacement Cassettes	Color
LDT596-250 (Part # 38830)	59, 6 and N48	RC596-250 (Part # 35241)	Red
LDT EUR (Part# 42009)	59, 6, N48 and Coax 9	RCEUR-250 (Part # 42004)	Orange
LDT MINI (Part # 38833)	MINI (22-24) and N35 AWG	RCMINI-250 (Part # 38587)	White
LDT MINI-125 (Part # 42590)	MINI (22-24) and N35 AWG	RCMINI-125 (Part # 42593)	Grey
*LDT MINI-1 (Part# 42310)	MINI (24-26 AWG)	RCMINI-250 (Part # 42314)	Tan
LDT MINI NS (Part # 38985)	MINI (24-26 AWG)	RCMINI-1-250 (Part # 38587)	White
LDT 6-PL (Part # 42313)	6 Plenum	RC 6PL-250 (Part # 42315)	Blue
LDT-UTP (Part # 42688)	CAT5, CAT 5E & CAT 6	RC-UTP (Part # 42687)	Yellow

\*LDT MINI-1 can only be used with CommScope® cable in the table below

### LDT MINI Model will prepare the following cables:

MINI Cable Manufacturer	Cable Identification
Beldon	*HC2650R, YR 46940, 1283, 1283S, *1279R, 1855, 1855A, *2648, 7534
Beta Cavi	N35
CommScope*	7534 #23AWG, 7538, 7538B, 7539/7539H, 73501S
Honeywell	5019, 5029, 5099
Times Fiber	T59M67T-VB, T59MQ65/40-VB

**Note: Please call customer service for additional information**