



Description: Hardline Connector, G052-F female Chassis.
(Measured with Cable Network CNA-540RB Cable)

DATA SHEET

Electrical

	Specification			Standard
Frequency Range	5 MHz – 3.000 MHz			
Impedance	75 Ω nominal			
	Better Than	Measured – Worst case of 5 measurements		
Return Loss	23 dB	≥ 26.2 dB	5 MHz – 500 MHz	IEC 61169-1
	22 dB	≥ 25.9 dB	500 MHz – 860 MHz	
	22 dB	≥ 26.4 dB	860 MHz – 1.000 MHz	
	16 dB	≥ 20.0 dB	1.000 MHz – 1.750 MHz	
	15 dB	≥ 18.3 dB	1.750 MHz – 2.150 MHz	
	15 dB	≥ 18.3 dB	2.150 MHz – 3.000 MHz	
Insertion Loss	0.13 dB	≤ 0.10 dB	5 MHz – 3.000 MHz	
Shielding Effectiveness of G052-FFC with 1m CNA-540RB cable (Measured with CoMeT)	Transfer Impedance @ 5 – 30 MHz		≤ 0.79 m Ω /item	IEC 62153-4-3
	Screening Attenuation @ 30 – 1.000 MHz		≥ 123.7 dB	IEC 62153-4-4
	Screening Attenuation @ 1.000 – 2.000 MHz		≥ 116.8 dB	IEC 62153-4-4
	Screening Attenuation @ 2.000 – 3.000 MHz		≥ 103.6 dB	IEC 62153-4-4
Common Path Distortion	≤ -110 dBc		ANSI/SCTE 109 2005	
Inner Conductor Resistance	≤ 3 m Ω @ 1 A DC.		IEC 61169-1	
Amp. Rating	≤ 4 A @ 60 V.			
Dielectric Strength	≥ 2 kV.		IEC 61169-1	
Insulation Resistance	≥ 29.99 G Ω @ 500 V.		IEC 61169-1	

Environmental

	Specification	Standard
Temperature range Operating	-40°C to +65°C	
Temperature range Installation	-5°C to +50°C	
Sealing Test	IPX8 – 1 meter / 24 hours	IEC 60529
Red Dye		ANSI/SCTE 60
Corrosion Protection		ASTM B 117-94

Mechanical

	Specification	Standard
Interface	F female	IEC 61169-24
Cable Retention	≥ 150 kgf	ANSI/SCTE 99

Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Inner conductor	NiSn (NITIN) plated Tinbronze	ASTM B605
Compression ring	NiSn (NITIN) plated Brass	ASTM B605
O'ring	EPDM	
Insulator	Polycarbonate/Polyethylene	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

Measurement setup:

G052-FFC – Cable – G052-FFC.

All measurements are done with Cable Network CNA-540RB cable, length 1.0 meter.

All results are the worst case result of measurement of 5 assemblies.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

CPD (Common Path Distortion) are measured with hp Spectrum Analyzer hp 8591E, according to SCTE standard.

In case of over current (≥ 4 A.) there is a risk for high temperature inside the connector, which can cause damage of the insulator, and / or the cable.

Further test reports, technical specifications and installation instructions can be obtained on request.

