



Description: Hardline Connector, PP540QR.  
(Measured with Cable Network CNA-540RB1 Cable.)

### DATA SHEET

#### Electrical

	Specification			Standard
Frequency Range	5 MHz – 3.000 MHz			
Impedance	75 $\Omega$ nominal			
	Better Than	Measured – Worst case of 5 measurements		
Return Loss Gated of PP540QR	28 dB 21 dB 19 dB 16 dB 14 dB 11 dB 17 dB	$\geq$ 31.3 dB $\geq$ 24.2 dB $\geq$ 22.1 dB $\geq$ 19.4 dB $\geq$ 17.4 dB $\geq$ 14.8 dB $\geq$ 20.4 dB	5 MHz – 500 MHz 500 MHz – 860 MHz 860 MHz – 1.000 MHz 1.000 MHz – 1.750 MHz 1.750 MHz – 2.150 MHz 2.150 MHz – 3.000 MHz 1.218 MHz	IEC 61169-1
Insertion Loss	0.13 dB	$\leq$ 0.10 dB	5 MHz – 3.000 MHz	
Shielding Effectiveness of PP-540QR with cable (Measured with CoMet)	Transfer Impedance @ 5 – 30 MHz $\leq$ 0.11 m $\Omega$ /m Screening Attenuation @ 30 – 1.000 MHz $\geq$ 121.8 dB Screening Attenuation @ 1.000 – 2.000 MHz $\geq$ 123.0 dB Screening Attenuation @ 2.000 – 3.000 MHz $\geq$ 122.7 dB Class: A++			IEC 62153-4-3 IEC 62153-4-4 IEC 62153-4-4 IEC 62153-4-4 EN 50117
Common Path Distortion	$\leq$ -110 dBc			ANSI/SCTE 109 2005
Inner Conductor Resistance	$\leq$ 1.0 m $\Omega$ @ 1 A DC.			IEC 61169-1
Amp. Rating	$\leq$ 15 A @ 60 V.			
Dielectric Strength	$\geq$ 3 kV.			IEC 61169-1
Insulation Resistance	$\geq$ 29.99 G $\Omega$ @ 500 V.			IEC 61169-1

#### Environmental

	Specification	Standard
Temperature range Operating	-40°C to +65°C	
Temperature range Installation	-5°C to +50°C	
Sealing Test	IPX8 – 1 meter / 24 hours	IEC 60529
Red Dye		ANSI/SCTE 60
Corrosion Protection		ASTM B 117-94

#### Mechanical

	Specification	Standard
Interface	5/8 male	ANSI/SCTE 92
Cable Retention	$\geq$ 150 kgf	ANSI/SCTE 99

#### Material and Finish

	Specification	Standard
Housing	Yellow Iregate plated Aluminium	MIL DTL-5541
Inner conductor	Ni (Nikkel) plated Brass	ASTM B605
O'ring	EPDM	
Insulator	Polyethylene	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

### **Measurement setup:**

Nm-58f, **PP540QR** – Cable – **PP540QR**, Nm-58f.

All measurements are done with Cable Network CNA-540RB cable, length 1.0 meter.

All results are the worst case result of measurement of 5 assemblies.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

CPD (Common Path Distortion) are measured with hp Spectrum Analyzer hp 8591E, according to SCTE standard.

In case of over current ( $\geq 15$  A.) there is a risk for high temperature inside the connector, which can cause damage of the insulator, and / or the cable.

Further test reports, technical specifications and installation instructions can be obtained on request.

