

Slack Storage Enclosures



The PPC family of enclosures offers a flexible and cost effective solution for fiber network deployments. Craft-friendly, expandable “grow as you go” designs support both greenfield and brownfield projects, and can be used either indoors or outdoors.

The SFIT (Stackable Fiber Interface Terminal) is the small-to-midsized solution; the UCS (Universal Closure System) handles the larger requirements. Both lines offer a variety of network functions.

Description

The PPC SFIT Slack Storage Housing provides a flexible solution for handling excess cable in fiber network deployments.

It can be used as a stand-alone box, or can be coupled to other SFIT enclosures for an integrated solution.

With a capacity of 100 feet of 5mm cable, the housing features a removable rear port that can be used to exit cable directly into a wall. Flat rubber grommets for three lower entry ports offer easy installation and protection. Also included are three rubber grommets used when coupling SFIT enclosures together, and two field-installable nozzles (upper and lower) for 1.25" PVC pipe.

Features

- Four 3.5 inch tall fiber guide spools for cable management
- Typical capacity of 100 feet of 5mm cable
- Large removable port in back provides access for cable or microduct
- Field-installable nozzles (upper and lower) for 1.25" PVC pipe
- Door has push-to-latch, locking hasp & 216-tool security bolt
- Three cable ports equipped with flat rubber grommets
- Molded-in feet for easy wall mounting
- Small footprint for use in tight spaces
- Stackable design allows coupling to other SFIT enclosures
- Includes 3 rubber grommets used when coupling SFITs
- Pole mountable with Pole Mount Bracket kit (SFIT- POLEMTG-10)
- Designed for indoor and outdoor use
- A variety of cable port nozzles are available



SFIT-FL00BNX-001

Specifications

Dimensions: 9.3" H x 10" W x 4.7" D

Materials: UL 94V-0 (indoor) and UL 94-5VA (outdoor) flame retardant PBT/PC blend thermoplastic

Safety: UL1863 cULus

Performance: Designed to meet GR-049-CORE, GR-3125-CORE & GR-2898-CORE

Finish: Light Gray

Part No.	Description
SFIT-FL00BNX-001	SFIT Slack Storage Housing - three cable entry ports with flat rubber grommets; rear port; 1.25" PVC pipe nozzles; stacking grommets

Slack Storage Enclosures



Description

The PPC UCS Slack Storage Housing is designed to handle larger cables and longer slack loops in fiber network deployments. It can be used as a stand-alone housing, or can be coupled to other UCS enclosures for an integrated solution.

The housing has provisions to handle two loops of cable. The outer loop, captured by four cut-and-loop straps, can be up to 100 ft of 0.4" OSP cable. An inner loop with four fiber spools can hold up to 30 ft of 3mm cable.

Four entry ports with removable caps (including one rubber cone grommet and ring-brush) offer flexibility for cable routing.

The housing can be stacked with other UCS terminals, such as a Patch Only Terminal, to provide an integrated solution.



UCS-FS00XXNN-JB

Features

- Manages two separate loops of slack cable:
 - Outer loop of up to 100 ft of 0.4" OSP cable
 - Inner loop of up to 30 ft of 3mm drop cable
- Outer loop retained by cut-and-loop straps; inner loop by plastic spools
- Door has push-to-latch, locking hasp & 216-tool security bolt (3)
- Four cable access ports with removable caps
- Ships with one rubber cone grommet/brush disk (UCS-G2)
- Includes four screw-on feet for easy wall mounting
- Can be pole-mounted with Pole Mount Bracket kit (UCS-PMB)
- Stackable design allows coupling with other UCS enclosures, using SCC-UUF coupler kit (one per port)
- Designed for indoor and outdoor use

Specifications

Dimensions: 13" H x 13" W x 8" D

Materials: UL 94V-0 (indoor) and UL 94-5VA (outdoor) flame retardant PBT/PC blend thermoplastic

Safety: UL1863 cULus

Performance: Designed to meet GR-049-CORE, GR-3125-CORE & GR-2898-CORE.

Finish: Light Gray

Part No.	Description
UCS-FS00XXNN-JB	UCS Slack Storage Housing - includes one rubber cone grommet port
UCS-G2	Cone Grommet Port Kit; includes ring brush (for one UCS port)
UCS-PMB	Pole Mount Bracket Kit for UCS
SCC-UUF	UCS Port Coupler kit – field installable. Kit couples one port (two kits needed to stack two UCS housings together)