



ShockDot impact indicators acts as a visual deterrent to improper handling.

Protect your investments. Drive down damages. Improve your margins.

ShockDot is a cost-effective solution that detects the mishandling of products and packages during shipment. Alerting handlers that a package is being monitored and requires extra care will ultimately reduce damage related costs. ShockDot indicators turn red when a potentially damaging impact occurs. The indicators are tamperproof and serialized to ensure the user that the device has not been switched during transport. The QR code on each label allows customers to verify that they have received the quality and reliability of an authentic ShockWatch product.

ShockDot indicators are a simple solution for identifying potentially damaged shipments and driving accountability in the supply chain.



Larger display for greater visibility

QR Code

Serial Number



Benefits:

- Provides indisputable evidence of mishandling
- Alerts recipient to inspect contents before acceptance
- Promotes chain of accountability for all product handling
- Confirms effectiveness of packaging
- Helps increase quality of product from dock to dock
- Verify authenticity of the ShockDot by scanning the QR code and entering in the serial number

VERIFY THE AUTHENTICITY OF YOUR SHOCKDOT.

Serial Number

Verify Authenticity

ShockDot impact indicators act as a visual deterrent to improper handling and can help reduce costs related to shipping damage.


ShockDot™ Impact Indicator

Interpreting the ShockDot

If a package has not been mishandled, the circular indicator in the center of the ShockDot will remain white. If the package has been dropped, the indicator will show full or partial red coloration. Any red in the ShockDot indicator window alerts receivers to inspect the package for potential damage.

Below are examples of ShockDot results:

No activation:



Activation:



Key Specifications	
Sensitivity range	25 - 100G
Impact duration	0.5 - 50ms
Tolerance	±15% at 20°C / 68°F, 1 ATM
Operating temperature	-25°C to 80°C / -13°F to 176°F
Weight (varies by sensitivity)	1.98g
Dimensions	3.8 in x 3.8 in / 96.52 mm x 96.52 mm
Security	Tamperproof, Serialized
Adhesive	Acrylic
Product life	2 years when stored at 20°C / 68°F, 1 ATM
Storage recommendations	20°C / 68°F, 1 ATM, 0-99% RH Non-condensing

Product Description	Part Number
100G (Green)*	SD-100G
75G (Orange)*	SD-75G
50G (Red)*	SD-50G
37G (Purple)*	SD-37G
25G (Yellow)*	SD-25G
Companion Label - 200/roll	26106
Companion Label - 500/roll	26107
*Minimum order quantity: 100	

ShockWatch can assist you in setting up a damage reduction program tailored to your unique circumstances. For more information, please contact your ShockWatch representative.

SHOCKWATCH®
SMART SOLUTIONS FOR SAFE TRANSIT

5501 LBJ Freeway, Suite 350, Dallas, TX 75240 • +1 214-736-4580 • 800-527-9497 • www.shockwatch.com