

FILM  
INSERT  
HERE

Interior Side

### Benefits and selection criteria

- Shields 99% of UV radiation, reducing fading of valuables, fabrics, and furnishings
- Durable scratch-resistant coating for easy cleaning
- Reduction of hot spots increases HVAC efficiency and lowers energy costs
- Improves building aesthetics
- Used where excellent glare and heat reduction are essential, combined with low reflectance and truly neutral transmitted daylight color balance

Manufacturer's  
Warranty

Contact your dealer  
about details

# FILM INSERT HERE

Exterior Side

## Performance Data

	% Total Solar Transmittance	% Total Solar Reflectance	% Total Solar Absorptance	% Visible Light Transmittance	% Visible Reflectance (exterior)	% Visible Reflectance (interior)	Winter U-value	Shading Coefficient	% Ultraviolet Ray Protection (wavelengths 280-380nm)	Emissivity	Solar Heat Gain Coefficient	% Total Solar Energy Rejected	Light-to-Solar Heat Gain Ratio (LSG)	% Summer Solar Heat Gain Reduction	% Winter Heat Loss Reduction	% Glare Reduction
Clear Glass 1/4" (6mm) single pane	77	7	16	88	8	8	1.03	0.94	38	0.84	0.82	19	1.07	-	-	-
Clear Glass 1/4" (6mm) dual pane	61	11	28	79	14	14	0.47	0.81	54	0.84	0.70	30	1.13	-	-	-
N1020 SR 1/4" (6mm) clear single pane	19	22	59	23	28	27	1.03	0.44	99	0.84	0.37	63	0.62	53	0	74
N1020 SR 1/4" (6mm) clear dual pane	15	21	64	21	30	27	0.47	0.55	99	0.84	0.47	53	0.45	32	0	73