



Maintenance Guidelines

Spa Frog

FRESH FILL (start-up)

1. Add (1 oz. per 100 gallons) of **SpaGuard Stain & Scale**.
2. Check and balance total alkalinity (125-150ppm)
Adjust as needed with **SpaGuard Total Alkalinity Increaser** or **SpaGuard pH Decreaser**.
3. Check and balance pH (7.4-7.6)
Adjust as need with **SpaGuard pH Increaser** or **SpaGuard pH Decreaser**.
4. Check and balance calcium hardness levels (100-200ppm)
Adjust as needed with **SpaGuard Calcium Hardness Increaser** or **Vanishing Act Calcium Remover** (if Calcium hardness is less than 100ppm DO NOT USE **Vanishing Act**).
5. When adjusting the pH, total alkalinity, and calcium hardness refer to the back label of the coordinating chemical bottle to calculate exact measurements to add in order to achieve the correct levels.
6. Add 3 tbsp. of **SpaGuard Enhanced Shock** (per 500 gallons of water) to jump start.
7. Set the Blue Mineral Cartridge to #6 (wide open). This cartridge will last 4 months.
8. Set the Yellow Bromine Cartridge to #6 for the first 24 hours ONLY. After 24 hours, turn the Yellow Bromine Cartridge down 1 setting everyday until a reading of approximately 1.0 ppm level is obtained.

REGULAR SPA CARE (WEEKLY)

1. Maintain a minimum of 1.0 ppm bromine level at all times.
2. Shock the spa once a week or as needed with **SpaGuard Enhanced Shock** (3 tbsp. per 500 gallons). Remember, while using Spa Frog the bromine level only needs to be between 1.0-2.0 ppm

REGULAR SPA CARE

1. Every 30 Days: Bring in your water to any Georgia Spa location and get your water tested to check your levels.
2. Regularly check water for pH, total alkalinity and bromine levels by using chemical test strips.
**Additional shocking may be required if the spa is under heavy use (more than 3 times a week)
3. Check your filters. If they appear dirty, use a filter cleaner and degreaser to clean them (**SpaGuard Filter Cleaner**). Best results are achieved when the filters are soaked in filter cleaner overnight. Be sure to rinse the filters before placing them back into the spa. Dirty filters may cause cloudy water, low jet pressure or FLO errors in your hot tub.

REPLACEMENT

Yellow: Replace the Yellow Bromine Cartridge when it is empty. The Yellow Cartridge will float on its side when it is empty. Drain the water from the cartridge to ensure it is empty and then discard in the trash. The cartridge life will vary depending on the size of the spa and the number of users. This cartridge will not last more than 4 weeks.

Blue: The Blue Cartridge MUST be replaced every 4 months. Chemicals are exhausted after 4 months regardless of how full the cartridge may sound.

MEASUREMENT KEY

3 teaspoons = 1 tablespoon

1 tablespoon = 0.5 ounce

8 ounces = 1 cup

ALPHARETTA • 7300 North Point Pkwy, Alpharetta, GA 30022 • (770) 932-9045
ATHENS • 1850 Epps Bridge Pkwy, Athens, GA 30606 • (706) 227-4522
AUGUSTA • 1257 Augusta West Pkwy, Augusta, GA 30909 • (706) 229-8827
BUFORD • 3480 Financial Center Way, Buford, GA 30519 • (770) 932-9061
KENNESAW • 955 Ernest W. Barrett Pkwy, Kennesaw, GA 30144 • (770) 795-8787
NEWNAN • 1068 Bullsboro Drive, Newnan, GA 30265 • (770) 755-1552
SERVICE & DISTRIBUTION • 1515 University Drive, Auburn, GA 30011 • (678) 383-2583