



SIMPLE
Water in, Water out



SAFE
Safer for the Environment,
Safer for your Employees



RELIABLE
Proven Chemistries,
Validated Application

DESCRIPTION

CL002P is designed for use as a closed cooling and heating loop system additive where a dry, powdered treatment is desired. **CL002P** contains a formulation of sodium molybdate, borate pH buffer, yellow metal corrosion inhibitor and polymer dispersant. **CL002P** is designed to be applied in closed loop system pot feeder equipment.

BENEFITS

- Minimizes transportation and handling costs.
- Eliminates drum disposal costs.
- Controls system from fouling.
- Minimizes corrosion in closed loop systems with mixed metals.

DIRECTIONS FOR USE

CL002P is used at a recommended dosage of 150 ppm as sodium molybdate in the system water. Average product dosage to deliver 150 ppm of sodium molybdate is 200 ppm as product. Mix product at a ratio of (2) 2lb bag of dry, powdered inhibitor to 5 gallons of water.

STORAGE & SHELF LIFE

Keep in a cool, dry place. Storage temperature should be 45°F to 95°F. Boxes stored in the appropriate manner have a shelf life of one year.

**Safety data sheets are available at msds.dober.com*



APPLICATION

CL002P is designed to be applied in closed loop system pot feeder equipment. Two 2lb bag will treat 2,400 gallons of system water.

For additional information contact Dober at:

630-410-7300

smartreleaseinfo@smartreleasetechnology.com

www.dober.com

DOBER