

TW-10

HYBRID FLOCCULANT

Description

HaloKlear's TW-10 is a unique hybrid dry flocculant specially formulated to effectively dewater high solid waste streams. The unique blend is designed to capture and separate sediment, heavy metals, and other contaminants from the water. The rapid settling of the captured contaminants allows for easy reuse of clean water.

Industry Applications

- Stormwater management
- Construction
- Remediation

Deployment Method

Dry application in closed loop or semi-closed loop system for drilling mud dewatering or wheel wash clarification. **TW-10** can be applied using several delivery methods, including dry auger feed system.

Packaging

Lot Number must be legible on each container. Container types: 275-gallon IBC tote with camlock or threaded outlet, 55-gallon drum or 5-gallon pail.

Handling and Storage

All containers must be free of leaks, damage, and gross contamination. Product should be maintained between 40°F and 90°F. Keep from freezing. Keep out of direct sunlight.

Product Benefits

- **Rapid Settling**
 - Accelerated floc formation with high shear strength
- **Highly Effective, Low Dose Formula**
 - Low cost liquids/solids separation
- **Easy On-site Storage & Handling**
 - Convenient to ship & easy to store dry product

Product Properties

Appearance	A clear pale amber, viscous liquid with a pungent odor of vinegar
Viscosity	4000 – 8000 cps
Specific Density	1.0 g/mL
pH	<4.5

Field Handling Recommendations

Check with your federal, state and local environmental regulators for rules and regulations regarding the use of this product. For more information, contact your Dober representative.

Safety Data

Before handling this material read the corresponding Material Safety Data Sheet for safety and health data.

For additional information contact Dober at:

(800) 323-4983

info@dober.com

www.dober.com/water_treatment

