

## GFT 6152 NATURAL COAGULANT

### Description

Dober's **GFT 6152** is a unique and versatile natural coagulant blend designed for effective use in the treatment of oil in water emulsions and separation of liquid and solid matter in wastewater. **GFT 6152** is designed to break any emulsion using less heat and less chemistry- typically without lowering pH levels- while cost effectively producing higher oil quality and cleaner effluent.

### Industry Applications

- Refining/Oil and Gas
- Auto
- Aluminum and Steel Mills
- Food

### Product Use and Dosage

Product use and dosage will vary based on specific applications. Please contact Dober for more information at (800) 323-4983 or [info@dober.com](mailto:info@dober.com).

### Product Benefits

- Superior oil and water separation
- Enhanced water clarity
- Higher oil quality
- Metals removal
- Lower solids generation
- Made from natural, sustainable materials
- Low use cost

### Product Properties

Appearance	Dark Brown Liquid
Density	1.200 – 1.300
Viscosity	200 – 500 cP
pH	3.00 – 4.00 s.u.

### Handling and Storage

As with any individual chemical, avoid prolonged contact with skin. In case of skin or eye contact, flush exposed area with large amounts of water. A SDS outlining proper handling of this product is available upon request.

### Packaging and Shipping

**GFT 6152** is available in 55 gallon drums, 275 gallon totes, and bulk.

### Safety Data

For safety and health data, please read the corresponding Safety Data Sheet. These are available upon request or at <http://msds.dobergroup.com/default.aspx>.