

LIQUIFLOC 3%

NATURAL FLOCCULANT

Description

HaloKlear LiquiFloc 3% is formulated from natural flocculants. The patented design and concentrated formula delivers superior and consistent performance and is biodegradable through enzymatic activity preventing bioaccumulation. **LiquiFloc 3%** has been tested and approved to Std. 60 for drinking water and has earned a General Use Level Designation (GULD) from the State of Washington Department of Ecology. **LiquiFloc 3%** can be used as a standalone product or in conjunction with HaloKlear DBP-2100 or LBP-2101 as part of the Dual Product System. It is ideal for cold climate applications where maintaining optimal viscosity is extremely important and is a practical solution for dosing smaller volumes of water.

Industry Applications

- Stormwater management
- Construction
- Environmental Remediation

Deployment Method

LiquiFloc 3% is typically deployed using metering pumps. **LiquiFloc 3%** can be applied using several delivery methods, including semi-passive and active systems.

Packaging

Lot Number must be legible on each container. Container types: 275-gallon IBC tote with camlock or threaded outlet or 55-gallon drum.

Product Benefits

- **Strongest Liquid Chitosan Formula Available**
- **Tested & Approved to Standard 60 for Drinking Water Treatment**
- **Ideal for Warm Climate or Climate-Controlled Applications**
- **Use Alone or as Part of the HaloKlear Dual Product System (DPS)**

Product Properties

Appearance	A clear pale amber, viscous liquid with a pungent odor of vinegar
Viscosity	4000 – 8000 cps
Specific Density	1.0 g/mL
pH	<4.5

Handling and Storage

All containers must be free of leaks, damage, and gross contamination. Product should be maintained between 40°F and 90°F. Keep from freezing. Keep out of direct sunlight.

Field Handling Recommendations

Check with your federal, state and local environmental regulators for rules and regulations regarding the use of this product. For more information, contact your Dober representative.

Safety Data

Before handling this material read the corresponding Material Safety Data Sheet for safety and health data.

For additional information contact Dober at:

(800) 323-4983

www.dober.com/haloklear/contact-us

The logo for Dober, featuring the word "DOBER" in a bold, blue, sans-serif font. The letter "O" is stylized with a white swirl inside it.