





ø140 - ø330 mm

ø5,5 to ø12,75 "

- Basic **stainless steel** jaws Ø8,5" to 12,75" ( Ø216 to Ø 330 mm )
- Included stainless steel auxiliary jaws Ø5,5" to Ø 10" ( Ø 140 to Ø 256 mm )
- **Cutting precision:** perpendicular cutting < 0.25 mm
- Dual-output cutting motor with 2 blade positions for uptake
- **Scalability:** may be transformed into a bevelling and orbital welding machine • Lifting eye
- **Weight:** 73 kg / 161 lbs (easy handling)



Optimized blade-jaws distance  
Limits vibration and tube distortion



Concentric clamping with 8 jaws in **stainless steel**, standard, to eliminate tube distortion



Motors: slow, fast, pneumatic



Rotation handle as **standard:** extends blade life and optimizes cutting quality

| References | Motors   | Accessories  | Consumables  |
|------------|--|--|--|
| 321FS29    | Motor 230V, mono :<br>FS29: Thickness Inox <5mm<br>FS25: Thickness Inox >5mm     | CCPS21: support feet   | LS6872 : 1 to 3 mm<br>LS6844 : 2 to 7 mm<br>LS8080: 1 to 3 mm<br>LS8054: 2 to 7 mm<br>LS8034 : 5 to 12 mm<br>LS9038 : 5 to 15 mm |
| 321FS19    | Motor 120V, mono :<br>FS19: Thickness Inox <5mm<br>FS15: Thickness Inox >5mm     | CCBSB-001: bench with height adjustment - 1.5 m<br>CCBSB-002: additional 1.5 m bench |  |
| 321FS25    |  |  |  |
| 321FS15    | MOPD: pneumatic 60 to 110 rpm, air flow rate 1500 l/min at 6 bar                 | SAEP-00 : electric rotation autoline 1CC21 to CC321 ( 120V - 230V )                  | LCA9028A : Carbide saw blades for carbon steel only thick. 4 to 15mm   |
| 321PD      | All motors are delivered in their individual case, including the necessary tools | CCSER1/CCSER2: simple/bearing stand  | CCLUH: lubricant   |

