


∅212 - ∅422 mm


∅8.625 to ∅ 16"

- Basic **stainless steel** jaws ∅ 12" to 16" (∅ 350 to ∅ 420 mm)
- Included stainless steel auxiliary jaws ∅ 8,625" to 12,75" (∅ 212 to ∅ 352 mm)
- **Cutting precision:** perpendicular cutting <0.4 mm
- Dual-output cutting motor with 2 blade positions for uptake
- Lifting eye

- **Weight:** 186 kg / 410 lbs



Optimized blade-jaws distance
Limits vibration and tube distortion



Concentric clamping with 8 jaws in **stainless steel**, standard, to eliminate tube distortion



Motors: electric and pneumatic



Rotation handle as **standard:** extends blade life and optimizes cutting quality

References	Motors	Accessories	Consumables
421FS15	Motor 230V, mono : FS29: Thickness Inox <5mm FS25: Thickness Inox >5mm	SAEP-000 : electric rotation autoline CC421 to CC721 (120V - 230V)	LS6872 : 1 to 3 mm LS6844 : 2 to 7 mm LS8080: 1 to 3 mm LS8054: 2 to 7 mm LS8034 : 5 to 12 mm LS9038 : 5 to 15 mm
421FS19	Motor 120V, mono : FS19: Thickness Inox <5mm FS15: Thickness Inox >5mm	On demand CCBSB2-003 : Adjustable height table for 421/521 and 721	
421FS25	MOPD: pneumatic 60 to 110 rpm, air flow rate 1500 l/min at 6 bar	CCBSB2-004 : Support bench - 1,5m module for 421 / 521 and 721	LCA9028A : Carbide saw blades for carbon steel only thick. 4 to 15mm
421FS29		CCBSB2-005 : Connection kit for bench CCBSB2	CCLUH: lubricant
421PD	All motors are delivered in their individual case, including the necessary tools		

