





ø312 - ø522 mm
ø12.75 to ø20 "

- Basic **stainless steel** jaws Ø 15,5" to 20" (Ø 450 to Ø 522 mm)
- Included stainless steel auxiliary jaws Ø 12,75" to 15,5" (Ø 312 to Ø 452 mm)
- **Cutting precision:** perpendicular cuts < 0.4 mm
- Dual-output cutting motor with 2 blade positions for uptake
- Lifting eye
- **Weight:** 223 kg / 492 lbs



Optimized blade-jaws distance
Limits vibration and tube distortion



Concentric clamping with 8 jaws in **stainless steel**, standard, to eliminate tube distortion



Motors: electric and pneumatic



Rotation handle as **standard:** extends blade life and optimizes cutting quality

References	Motors	Accessories	Consumables
521FS15	Motor 230V, mono : FS29: Thickness Inox <5mm FS25: Thickness Inox >5mm	SAEP-000 : electric rotation autoline CC421 to CC721 (120V - 230V)	LS6872 : 1 to 3 mm LS6844 : 2 to 7 mm LS8080: 1 to 3 mm LS8054: 2 to 7 mm LS8034 : 5 to 12 mm LS9038 : 5 to 15 mm
521FS19	Motor 120V, mono : FS19: Thickness Inox <5mm FS15: Thickness Inox >5mm	On demand CCBSB2-003 : Adjustable height table for 421/521 and 721	
521FS25	MOPD: pneumatic 60 to 110 rpm, air flow rate 1500 l/min at 6 bar	CCBSB2-004 : Support bench - 1,5m module for 421 / 521 and 721	LCA9028A : Carbide saw blades for carbon steel only thick. 4 to 15mm
521FS29		CCBSB2-005 : Connection kit for bench CCBSB2	CCLUH: lubricant
521PD	All motors are delivered in their individual case, including the necessary tools		

