



Ø33 - Ø170 mm
 Ø1,25 to Ø6,625 "

- Basic jaws Ø 2,75" to 6,625" (Ø70 to Ø170 mm)
- Included stainless steel auxiliary jaws Ø 0,625" to 4,65" (Ø 33 to Ø 118 mm)

- Supplied with plastic protection and profile guide
- **Technology:** screw carbide inserts: 10 x faster than HSS tools. Superior service life
- Max 8 mm according to spinner*


- Patented System

- **Scalability:** may be transformed into a cutting and orbital welding machine

- **Weight:** 44 kg / 97 lbs (easy handling)




V bevel with profile guide roller



J bevel with profile guide roller



Outer profile guide system: to account for tube "out of round"



Rotation handle as standard: extends blade life and optimizes cutting quality

References	Motors	Accessories	Consumables
GA171-2	GA10-220 : 230V mono	CCPS21 : support feet CCBSB-001: bench with height adjustment - 1.5 m CCBSB-002: additional 1.5 m bench CCSA21 : Pneumatic clamping for 121/171/221 and DC115-BM / DC221-BM	PC30-08-B02: carbide inserts TV-300: 30° spinner (Max 8mm) TV-375: 37.5° spinner (Max 7mm) TV-450: 45° spinner (Max 6,5mm)
GA171-1	GA10-110 :120V mono	SAEP-00 : electric rotation autoline 121 to 321 (120V - 230V) CCSER1/CCSER2: simple/bearing stand All motors are delivered in their individual case, including the necessary tools	TJ-100: 10° spinner with 6 rollers (Max 8mm) All spinner are delivered with their carbide inserts mounted

