

STEAM GENERATOR CONTROL KIT

SPECIFICATION SHEET

MODEL: KT60 3-BUTTON DIGITAL CONTROL
FOR USE WITH AK STEAM GENERATOR

Features

- 3-button digital control with on/off, temperature and time duration setting.
- Display alternates between ambient room temperature and time remaining.
- Features separate, remote mounted temperature sensor.

Installation

- Control mounts either inside steam room only.
- Control housing to be mounted in 2 3/8" diameter hole in wall.
- Temperature sensor mounts in 7/8" diameter hole located 6" down from 84" ceiling.
- Control and sensor cables connect to PCA inside steam generator.

Item Number

Digital Steam control Kit with control, sensor, cables and ComfortFlo steam head.

~~9111-101 KT60-CP Chrome~~

9111-105 KT60-PN Polished Nickel

9111-106 KT60-BN Brushed Nickel

9111-107 KT60-ORB Oil Rubbed Bronze

9111-108 KT60-BB Brushed Bronze

9111-109 KT60-MB Matte Black

May be used with a K60 as a second control.

Only one KT60 may be installed and it must be mounted in the steam room.

Not intended for use as installation instructions.
Refer to specific generator model installation instructions for further detail.

INSTALLATION VIEW



K60 Digital Control
3" H x 3" W x 1/4" D



ComfortFlo Steam Head
2-3/4" H x 3" W x 1-7/16" D

AMEREC STEAM

P.O. Box 2258 | 17683 128th Place NE, #C | Woodinville, WA 98072, USA

Toll-Free 1-800-331-0349

amerec@amerec.com | www.amerec.com

Amerec reserves the right to change specifications and design without notice.

© 2019 Amerec Steam

amerec[®]
STEAM. SAUNA. SOLUTIONS.