



FEATURES

- ✓ SMD Construction
- ✓ Standard 5X3.2mm Package Size
- ✓ Mil-Std-202 Compliant
- ✓ CMOS/TTL Output


Crystal Oscillator

#blileytakesyoufurther






Part Number Configuration

*Not all combinations of options may be possible

**Other options may be available



Physical Specifications



PIN	FUNCTION
1	Output Control
2	Ground
3	RF Output
4	Supply Voltage

Tolerances (mm) .X = ± 0.5, .XX = ± 0.2 unless otherwise specified



Notes

- 1) Connection Pads: Gold(10-40 μ in.) over Nickel (100-250 μ in.)
- 2) Weight = 1.5gms typical

Performance Specifications

Parameter	Conditions	Values			Unit
		MIN	TYP	MAX	
General		MIN	TYP	MAX	Vdc
Frequency Range	(and 32.768kHz)	1.0		150.0	MHz
Frequency Stability	Over Temperature Range	±25, ±50, ±100			ppm
Supply Voltage(Vdd)	Option B	1.62	1.8	1.98	Vdc
	Option D	2.97	3.3	3.63	Vdc
	Option E	4.5	5.0	5.5	Vdc
Current Consumption	@10MHz		15	20	mA
	@100MHz		45	60	mA
Output Control	Enabled-High Disabled-Low				
Startup Time			10		mSec


Parameter	Conditions	Values			Unit
		MIN	TYP	MAX	
Output Characteristics (CMOS/TTL)		MIN	TYP	MAX	
High Output Level	Logic 1	90% Vdd			Vdc
Low Output Level	Logic 0			10% Vdd	Vdc
Rise/Fall Time	10% ↔ 90%		8	10	nSec
Duty Cycle		40	50	60	%
Load	CMOS		15		pF
	TTL		10		pF

Parameter	Conditions	Values			Unit
		MIN	TYP	MAX	
Environmental		MIN	TYP	MAX	
Operating Temperature	Option B	-20		+70	°C
Operating Temperature	Option C	-40		+85	°C
Storage Temperature		-55		+125	°C
Seal	MIL-STD-202 Method 112 Test Condition C & D				

DISCLAIMER: Bliley Technologies, Inc. reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No intellectual property rights accompany the sale or delivery of any such product(s) or information.

Tape and Reel

Embossed Carrier Dimensions (8mm, 12mm, 16mm, 24mm Tape Only)



Tape Dimensions (mm)

Reel Dimensions (mm)

W	F	Do	Po	P1	P2	B1	T2	Outside Dia.	Parts / Reel
12	5.5	1.5	4.0	8	2.0	5.5	1.7	180	1,000

Recommended Reflow Profile

Reflow Profile: in accordance to IPC/JEDEC J-STD-020 (Latest Revision)

Additional Notes:

- This part has been designed for pick and place reflow soldering
- This part may be reflowed once
- This part should not be reflowed in the inverted position

Packaging

Packaging: All packaging must conform to ESD Controls detailed in ANSI/ESD S20.20 (Latest Revision)