

**FEATURES**

- ✓ Wide Operating Temperature Range
- ✓ Standard 5x3.2mm Package
- ✓ Rugged Hermetically Sealed Package
- ✓ Mil-Std-202 Compliant

**Voltage Controlled Oscillator**

#blileytakesyoufurther


**Description**

Voltage Controlled Oscillators are designed to meet the rigorous demands of Military Standards as well as provide long life to OEM equipment manufacturers. Bliley Engineers Concurrent Design philosophy provides robust designs which are economical as well as reliable for long-term life. Applications consist of SATCOM, TELECOM, Military and Instrumentation.

**Block Diagram**



**Part Number Configuration**



\*Not all combinations of options may be possible  
 \*\*Other options may be available

## Performance Specifications

Parameter	Conditions	Values			Unit
		MIN	TYP	MAX	
Frequency Range		10		170	MHz
Frequency Stability					
vs. Temperature	See Options (Max) Referenced to +25°C		±25, ±50, ±100		ppm
vs. Load	5% Change			±1	ppm
vs. Supply Voltage	5% Change			±1	ppm
Perturbation	Per 1°C			±3	ppm
Aging	1 <sup>st</sup> Year			±3	ppm
Supply Voltage	Option G	2.37	2.5	2.63	Vdc
	Option D	3.13	3.3	3.47	Vdc
	Option E	4.75	5	5.25	Vdc
Current Consumption			15	40	mA
Output Control	Enable – High, Open Disable - Low	30% Vdd		70% Vdd	Vdc
Electronic Frequency Control					
Voltage Range	3.3Vdc	0.3	1.65	3.0	Vdc
	5.0Vdc	0.5	2.5	4.5	Vdc
	2.5Vdc	0.2	1.25	2.3	Vdc
Frequency Range	See Options (Min)		±50, ±100		ppm
Slope			positive		
Input Impedance			5		MΩ
Linearity			10		%
Start Up Time				10	mSec

## Performance Specifications

Parameter	Conditions	Values			Unit
		MIN	TYP	MAX	
Output Characteristics					
High Output Level	Logic "1"	90% Vdd			Vdc
Low Output Level	Logic "0"	10% Vdd			Vdc
Rise/Fall Time		5			nSec
Duty Cycle		45	50	55	%
Load		15			pF




Parameter	Conditions	Values		Unit
		TYP	TYP	
Phase Noise				
Phase Noise (100MHz @ 25°C)	Offset	PLL	Non-PLL	
Phase Jitter	12KHz-20MHz RMS	1.0	0.5	pSec

# Environmental Compliance


Parameter	Conditions	Values			Unit
		MIN	TYP	MAX	
Operating Temperature	Option B	-20		+70	°C
	Option C	-40		+85	°C
Storage Temperature		-45		+90	°C
Solderability	MIL-STD-202 Method 208				
Shock	MIL-STD-202 Method 213 Test Condition A				
Vibration	MIL-STD-202 Method 204 Test Condition C				
Seal	MIL-STD-202 Method 112 Test Condition C & D				

**DISCLAIMER:** Bliley Technologies, Inc. reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No intellectual property rights accompany the sale or delivery of any such product(s) or information.

# Physical Specifications



Recommended Landing Pattern



PIN	FUNCTION
1	EFC/N.C.
2	Output Control
3	Ground
4	RF Output
5	N.C.
6	Supply Voltage


Tolerances (mm) .X = ± 0.5, .XX = ± 0.2 unless otherwise specified

Notes  
1) None

DISCLAIMER: Bliley Technologies, Inc. reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No intellectual property rights accompany the sale or delivery of any such product(s) or information.

# Tape and Reel

Embossed Carrier Dimensions (8mm, 12mm, 16mm, 24mm Tape Only)



Tape Dimensions (mm)							Reel Dimensions (mm)		
W	F	Do	Po	P1	P2	B1	T2	Outside Dia.	Parts / Reel
12	5.5	1.5	4.0	8	2.0	5.5	1.7	330	3000

# Recommended Reflow Profile

**Reflow Profile:** in accordance to IPC/JEDEC J-STD-020 (Latest Revision)

**Additional Notes:**

- This part has been designed for pick and place reflow soldering
- This part may be reflowed once
- This part should not be reflowed in the inverted position

# Packaging

**Packaging:** All packaging must conform to ESD Controls detailed in ANSI/ESD S20.20 (Latest Revision)