



Mining And Surface Certification (Pty) Ltd

2015/021934/07



Certificate Number: MASC M/11-290
Issue: 28 July 2017
Expire: 28 July 2020
Page: 1 of 3

IA – CERTIFICATE

(Supplement 2: Supplemented as per ARP 0108)

IN TERMS OF REGULATION 21.17.2 OF THE MINERALS ACT (INCORPORATION THE MINE HEALTH AND SAFETY ACT) AND REGULATION 9 (1) OF THE ELECTRICAL MACHINERY REGULATIONS OF THE OCCUPATIONAL HEALTH AND SAFETY ACT

Ex – Type Examination

Certificate number:

Equipment:

Serial No:

MASC M/11-290

TX2121 Single Port Isolator

(See “Conditions of Certification”)

Applicant:

Address:

Troxel Limited.

Hazel Grove

Stockport

Cheshire

SK7 5DY

United Kingdom

Manufacturer:

Address:

Troxel Limited.

Hazel Grove

Stockport

Cheshire

SK7 5DY

United Kingdom

DESCRIPTION:

The TX2121 Single Port Isolator is designed to take a single serial communications interface and repeat it via an isolated interface. The TX2121 Single Port Isolator is mounted in the non-hazardous area and provides an intrinsically safe serial interface into the hazardous area.

The apparatus consists of two PCB's mounted within a plastic DIN rail mounted enclosure. The TX2121 Single Port Isolator measures approximately 105mm x 85mm x 60mm. On the side of the enclosure is an eight way DIL switch block used to set the address of the repeater. LED indicators are situated on top of the enclosure indicating power and communications status.

Electrical connections to the apparatus are made via screw terminals. The TX2121 Single Port Isolator is intended to be mounted in a separate outer enclosure offering additional protection suitable for mining environment.

Power connections: CN101/7 w.r.t CN101/5 (0V)

$U_m = 253V_{rms}$

The circuit connected to the non-hazardous area terminals is designed to operate from a nominal supply voltage of 12Vdc.

/ . Serial interface...

This document may only be reproduced in full.

This certificate is not transferable and remains the property of the issuing body.

This document will not be supported by MASC for certification purposes outside the borders of South Africa.

Mining And Surface Certification (Pty) Ltd Reg No: 2015/021934/07

Directors: Roelof Viljoen & Francois du Toit

Unit #5, Lelyta Park, 45 Jurg Avenue, Hennospark Ext 87, Centurion, 0157 ♦ P.O. Box 14344, Clubview, 0014

Tel: 012 653 2959 ♦ Fax: 086 605 8568

e-mail: info@masc-ex.co.za

IA CERTIFICATE NUMBER: MASC M/11-290
TX2121 Single Port Isolator

Page 2 of 3

Serial interface connections: CN101/1 and CN101/3 w.r.t 0V (CN101/5)

$U_m = 253V_{rms}$

The circuit connected to the non-hazardous area terminals is designed to operate from a nominal supply voltage of 5Vdc

1. Hazardous Area Terminals

Power Connections: CN201/7 w.r.t CN201/5 (0V)

$U_i = 14.4V$

$I_i = 3.33A$

$C_i = 6.86\mu F$

$L_i = 0$

Serial Interface Connections: CN201/1 and CN201/3 w.r.t 0V (CN101/5)

$U_i = 5.66V$

$I_o = 65mA$

$P_o = 0.208W$

$U_i = 6.88V$

$C_i = 1.08\mu F$

$L_i = 0$

$C_o = 130\mu F$

$L_o = 50mH$

$L_o/R_o = 3355\mu H\Omega$

MARKING:

BASEEFA marking remains applicable. The following MASC Certificate number (IA number) must be additionally applied to the equipment.

IA No: MASC M/11-290

COMPLIANCE:

The equipment as described above and in MASC letter 11-290 R2 is hereby certified "Explosion Protected" [Ex ia] I (-20°C <Ta<+50°C) and is suitable for use in hazardous locations as stated below and as tested, assessed and inspected in accordance with the relevant requirements of SANS / IEC Standards:

The evaluation was conducted according to the requirements of:

- i) SANS (IEC) 60079-0 : 2006 "Explosive atmospheres – Part 0: Equipment — General requirements"
- ii) SANS (IEC) 60079-11 : 2007 "Explosive atmospheres – Part 11: Equipment protection by intrinsic safety 'i'"

Location	Zone *0, 1 & 2	Gas/ Coal dust: Underground
Hazard Frequency	---	Continuous as could occur under normal operating conditions in hazardous area (*Outputs only)
Environment	Group I	Methane and coal dust
Surface Temperature	150°C	
Service/Ambient Temperature	-20°C to 50°C	Ambient Temperature

/./ The use...

This document may only be reproduced in full.
This certificate is not transferable and remains the property of the issuing body.
This document will not be supported by MASC for certification purposes outside the borders of South Africa.

The use of apparatus in hazardous locations is subject to the following provisions as applicable, which shall be adhered to:

- i. SANS 10086 requirements;
- ii. Any conditions mentioned in the above document;
- iii. Codes of Practice enforced in terms of Regulations 21.17.2 of Minerals Act, by Chief Inspector of Mines;
- iv. Any restrictions and conditions enforced by Chief Inspectors of Mines, Principal Inspector (Group I equipment) of Chief Inspector of Factories (Group II equipment);
- v. Any relevant requirements of the MHS Act or the OHS Act.

CONDITIONS OF MANUFACTURE:


- None

SPECIAL CONDITIONS OF USE (X):


- None

CONDITIONS OF CERTIFICATION:

1. This Certificate remains valid based on a three yearly review covered by an official MASC letter.
2. The apparatus must be additionally marked with the MASC marking details above.
3. This approval only covers the equipment as certified above and does not include any scheduled additions or variations / amendments / new issues to the certificate(s), made after the above date.
4. The equipment does not need to be re-tested when used on the conditions and with such restrictions as prescribed by BASEEFA and in this approval.
5. The BASEEFA certification must remain valid.
6. The extent of the requirements in the ARP 0108 (or regulations) and SANS 10108 on the certification of the equipment must remain unchanged.
7. The Ex quality assurance notification/report for the equipment must remain valid.



A. Koekemoer
TECHNICAL SPECIALIST



F du Toit
TECHNICAL SPECIALIST

Mining And Surface Certification

This document is issued based on Mining And Surface Certification's Standard Contract terms and conditions available on request.

While every endeavour is made to ensure that a test / assessment is representative and accurately performed, and that a report is accurate in the quoted results and conclusions drawn from the test / assessment, MASC or its members/employees shall in no way be liable for any error made in carrying out the test / assessment or for any erroneous statement, whether in fact or in opinion, contained in a report issued pursuant to a test / assessment.

MASC takes no responsibility for any non-conformances, exclusions or any results / assessments not in compliance with the standards. By marking the equipment in accordance with the documentation / standard, the manufacturer attests on his own responsibility that the equipment has been constructed in accordance with the applicable requirements of the relevant standards and that the routine verifications and routine tests have been successfully completed and the product complies with the documentation and standard(s).

This document is only for use and application in South Africa. It is issued based on National interpretations and accepted practises.

This document may only be reproduced in full.
This certificate is not transferable and remains the property of the issuing body.
This document will not be supported by MASC for certification purposes outside the borders of South Africa.