

MILBANK PORTABLE GENERATORS

POWER YOU CAN DEPEND ON

From campsite to job site, from tent to trailer, and all points in between, Milbank's rugged, dependable portable generators put the power in your hands to get the job done. From 3250W to 7500W, trust in Milbank's comprehensive line of EPA-compliant portable generator solutions to deliver power when you want it, wherever you need it.







The Complete Package – Includes everything you need in one box to hit the ground running – wheel kit, handle kit (some assembly required), oil, funnel, and tool kit

Quiet Operation – The Pulse–Flo muffler allows us to boast one of the quietest generators on the market

Exclusive VR System – Voltage–regulated power protection for all your electronic needs

Iron–Sleeved Engine – Our engine sleeves are made with cast iron for long–lasting durability and low maintenance

Simplified Operator Control Center – Clean, simple and easy to use to harness the power you need, when you need it.





MILBANK PORTABLE GENERATORS

| SPECIFICATION | NS | | | | | |
|--|---------------------|---|---|---|---|---|
| Model Number | MPG32501 | MPG55003 | MPG6000S | MPG6500E | MPG70002E | MPG75002E |
| Starting | Manual | Manual | Manual | Electric | Electric | Electric |
| Rated Watts | 3250 Watts | 5500 Watts | 6000 Watts | 6500 Watts | 7000 Watts | 7500 Watts |
| Surge Watts | 3750 Watts | 6750 Watts | 7500 Watts | 8000 Watts | 8500 Watts | 9000 Watts |
| Run Time @½ Load | 14 Hours | 13 Hours | 12 Hours | 12 Hours | 11 Hours | 11 Hours |
| Engine | OHV, 4-Stroke | OHV, 4-Stroke | OHV, 4-Stroke | OHV, 4-Stroke | OHV, 4-Stroke | OHV, 4-Stroke |
| Engine Displacement | 208cc | 357cc | 357cc | 420cc | 420cc | 420cc |
| EPA Compliant | Yes | Yes | Yes | Yes | Yes | Yes |
| Fuel Tank Capacity | 4.0 Gallons | 6.6 Gallons | 6.6 Gallons | 6.6 Gallons | 6.6 Gallons | 6.6 Gallons |
| Low Oil Shutdown | Yes | Yes | Yes | Yes | Yes | Yes |
| Automatic Fuel Shut-Off | Manual | Yes | Yes | Yes | Yes | Yes |
| Excitation | Brush | Brush | Brush | Brush | Brush | Brush |
| Unit Dimensions L x W x H (inches) | 23.7 x 16.9 x 16.7 | 27.2 x 20.5 x 22 |
| Unit Weight | 100 lbs | 172 lbs | 183 lbs | 193 lbs | 194 lbs | 199 lbs |
| Carton Dimensions L x W x H (inches) | 27.17 x 18.1 x 18.3 | 31.5 x 21.4 x 23.2 |
| Shipping Weight | 108 lbs | 184 lbs | 195 lbs | 205 lbs | 206 lbs | 211 lbs |
| Outlets (Quantity / Type) | 4 / 5-20R 120V | 4 / 5-20R 120V 1 / L14-30R 120/240 Twist Lock | 4 / 5-20R 120V 1 / L14-30R 120/240 Twist Lock | 4 / 5-20R 120V 1 / L14-30R 120/240 Twist Lock | 4 / 5-20R 120V 1 / L14-30R 120/240 Twist Lock | 4 / 5-20R 120V 1 / L14-30R 120/240 Twist Lock |
| Oil Bottle (One bottle sized for en- gine: SAE10W30) | Yes | Yes | Yes | Yes | Yes | Yes |
| Oil Funnel | Yes | Yes | Yes | Yes | Yes | Yes |
| Multi-Outlet 25' Power Cord* | No | No | Yes | No | No | No |
| Battery | No | No | No | Yes | Yes | Yes |
| Wheel Kit | Yes | Yes | Yes | Yes | Yes | Yes |
| Tool Kit | Yes | Yes | Yes | Yes | Yes | Yes |
| Fuel Gauge | Yes | Yes | Yes | Yes | Yes | Yes |
| Hour Meter | No | No | No | No | Yes | Yes |

Running engines give off carbon monoxide, an odorless, colorless, poisonous gas so it is important to keep exhaust gas away from any windows, doors, ventilation intakes or crawl spaces. Not for indoor use. Milbank reserves the right to make changes in specifications and features shown without notice or discontinue the product described at any time without notice or obligation.