

WST-630T WIRELESS INTERLINK SMOKE ALARM

THERMOPTEK®

Wi-Safe® 2



10 year sealed in power pack
removes the need to replace the batteries

Diameter 132mm

Depth 40.50mm

Weight 210g



Weight: 210g

Product Features

- Thermoptek Multi-Sensor technology for fast detection of all fire types
- 10 year sealed for life battery
- Wirelessly interlink up to 50 Wi-Safe 2 smoke/heat/CO alarms and accessories on a single network
- Sealed for life tamper-proof lithium battery
- Large central button - Test / Smart Silence / Locate
- Locate feature - when the network goes into alarm pressing the test button of any alarm will silence all but the initiating alarm
- Easy to install with automatic battery engagement on base plate
- Smart Silence - allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm. During these 10 minutes if additional smoke is detected the alarm will sound

Technical Specification

Power	10 year sealed for life lithium battery
Technology	Thermoptek and Wi-Safe 2
Alarm sound level	85dB at 3m
Operation	DC
Installation positions	Ceiling / Wall
Operating temperature	+4°C to +38°C
Operating humidity	Up to 90% RH non-condensing
Storage temperature	+4°C to +38°C
Storage humidity	Up to 93% RH non-condensing
Warranty	5 years
Master pack quantity	10
Approvals	EN 14604: 2005
Max No. of connected units	50 units
Networking	Multi-directional communication
Compatibility	Compatible with all products containing Wi-Safe 2, including use in mixed systems (ie of mains and battery powered products).
Independently tested to	ETSI EN 300 220-2 V2.3.2 (2010-02) by TRaC
Range	35m (over 200m in clear air)
EAN	0816317001956
Packaging	Full colour printed cardboard box, in outer boxes of 10

CE₁₂
0832
Smoke alarm devices
EN 14604:2005

