Chevy LS2K 12° FLAT TOP SERIES



- 3D milling on piston crowns for ready to install finish Inboard forging design with fully machined under crown for maximum strength
- Valve pockets designed to work with most aftermarket 12° cylinder heads
- Side gas ports for better ring seal
 Moly skirt coating for friction loss and skirt wear protection
 Top ring down dimension: .280" (1.115cd) .250" (1.053cd)
- Ratios figured for .053 head gasket
- Premium 1.5mm x 1.5mm x 3.0mm ring package included
- Premium H-13 .225W wrist pins included chamfered for round wire locks
- Valve pocket depth: 0.220" intake and .162" exhaust
- 2618 material for High HP-NOS-Boost applications rated for 2000HP

Designed For Use With OEM and Aftermarket Blocks COMPRESSION RATIO											
Bore	Stroke	Rod	C.D.	Weight	Pin	CC's	62cc	70cc	76cc	Ring Set	Part #
4.000	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	10.6	10.4	10.2	09054005	21523-RS
4.005	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	10.6	10.4	10.2	09054005	21524-RS
4.010	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	10.6	10.4	10.2	09024010	21525-RS
4.030	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	10.7	10.5	10.3	09054030	21526-RS
4.035	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	10.8	10.5	10.3	09054030	21527-RS
4.065	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	10.9	10.7	10.5	09054065	21528-RS
4.070	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	10.9	10.7	10.5	09054070	21529-RS
4.080	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	11.0	10.8	10.5	09054080	21530-RS
4.125	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	11.2	11.0	10.7	09054125	21531-RS
4.185	4.000	6.125	1.115	call	.927 x 2.250	-4.8cc	11.5	11.3	11.0	09054185	21532-RS
4.030	4.125	6.125	1.053	call	.927 x 2.250	-4.8cc	11.0	10.8	10.6	09054030	21533-RS
4.070	4.125	6.125	1.053	call	.927 x 2.250	-4.8cc	11.2	11.0	10.8	09054070	21534-RS
4.125	4.125	6.125	1.053	call	.927 x 2.250	-4.8cc	11.5	11.3	11.1	09054125	21535-RS

Optional H-13, M2 and TP-1 wrist pins available as a upgrade to any piston part number. Contact Diamond Pistons for tech assistance.



