

OVERWRAPPER FOR CLEAR FILM

AND NO WASTE

For full production lines including Retail Rolled products such as posters, wrapping paper and other papers. Flat pack packaging as well.

OW Series

Clear film overwrapping

No film waste - full width of film is used; no edge trim required

Adjustable thermal impulse seal wire system

Powered overwrap film unwind

Demand film feed length control\

Preliminary shrink heat control

Full Size shrink tunnel

Quick changeover for diameter and width



Available Overwrapper Models

MODELS	OW-30-C	OW-36-C	OW-30-CE*	OW-42-C	OW-48-C
Roll Width	12-30 in. (30.5-76.2 cm)	18-36 in. (45.7-91.4cm)	12-30 in. (30.5-76.2cm)	18-42 in. (45.7-106.7cm)	24-48 in. (61.0-122.0cm)
Production Speed	50	35	30	30	25
Roll Diameter Optional	1 1/4- 3 1/2" (31.8-88.9mm) 2 5/8 - 5" (66.7 - 127 mm)	1 1/4 - 3 1/2" (31.8 - 88.9 mm) 2 5/8" - 5" (66.7 - 127 mm)	1 1/4 - 3 1/2" (31.8 - 88.9 mm)	1 1/4 - 4" (31.8 - 102 mm)	2.0 - 6.0" (50.8 - 152.4 mm)
Film Gage	.00060 inch (.015 mm) minimum to . 0015 inch (.038 mm) maximum thickness	.00060 inch (.015 mm) minimum to . 0015 inch (.038 mm) maximum thickness	.00060 inch (.015 mm) minimum to . 0015 inch (.038 mm) maximum thickness	.00060 inch (.015 mm) minimum to . 0015 inch (.038 mm) maximum thickness	.00060 inch (.015 mm) minimum to . 0015 inch (.038 mm) maximum thickness
Film Type	Heat shrinkable, heat sealable, preferentially oriented PVC or Polyolefin				
NOTE: *Model OW-30-CE has sealed ends to protect product					

PURPOSE BUILT PRECISION



You get the right machine for the job at hand. Plus hands-on service and support for the life of your machine from the experts behind them. That means more up-time and peace of mind than ever.