



1. PRODUCT NAME

Rust-O-Guard Rust Preventative

2. MANUFACTURER

The Hill and Griffith Company
1085 Summer Street
Cincinnati, OH 45204
Toll-Free: 1-800-543-0425

3. PRODUCT DESCRIPTION

Basic Use: Rust-O-Guard is a rust-preventative material that is applied to steel forms to prevent the formation of rust and corrosion on forms in storage, either outside or inside. It also waterproofs wood forms in storage. Protection time is 6 to 8 months.

Composition: Rust-O-Guard Rust Preventative is a paraffin-like material in a hydrocarbon carrier.

4. TECHNICAL DATA

Physical Properties are:

Flash Point..... 120°F
Boiling Point..... over 240°F
Freeze Temperature.....-15°F
Freeze Damage..... None
Wt./Gal..... 6.89 lbs
Viscosity(Centistokes).. 22.5 @ 40°C
Color..... Brown
Solubility in Water..... Insoluble
VOC Content..... 450 Grams/Liter
(3.8 Lbs./Gal.)

5. APPLICATION

Methods: Rust-O-Guard Rust Preventative must be agitated or stirred thoroughly before use and occasionally during use.

It should be applied by roller, mop, brush, or any conventional method so that surfaces are coated well. It applies easiest at temperatures above 50° F. Application equipment should be cleaned after use with solvent.

When forms are put back into service, Rust-O-Guard can be easily removed using naphtha, diesel fuel, or other solvent and wiping it off. Forms are then ready for the release agent.

Coverages: On smooth, non-porous form surfaces 500 sq. Ft./Gal. on semi-porous wood surfaces – 300 Sq. Ft./Gal.

Precautions: Keep out of reach of children. Do not take internally. Do not use near fire or open flame. Use with adequate ventilation and avoid prolonged contact with skin.

6. AVAILABILITY AND COST

Availability: Rust-O-Guard is available in 55, 5, and 1 gallon containers.

Cost: Material costs can be obtained from: The Hill and Griffith Company, Inc.

7. LIMITED WARRANTY

The manufacturer warrants the product against defects in composition. If the manufacturer receives notice of such defects, the manufacturer may at his option either replace the product or refund the purchase price. The warranty set forth is exclusive and no other warranty, whether written or oral, is expressed or implied. The manufacturer specifically disclaims the warranties of suitability and fitness for a particular purpose. The final responsibility for the suitability and fitness for a particular purpose lie with the purchaser.

8. MAINTENANCE

Storage: Rust-O-Guard will keep indefinitely in sealed containers. It must be stirred between each use.

9. TECHNICAL SERVICES

Technical information is available by contacting:

The Hill and Griffith Company
1085 Summer Street
Cincinnati, OH 45204
Phone: 1-800-543-0425
Fax: 513-244-4199
Email: sales@hillandgriffith.com
www.hillandgriffith.com