

**Technical  
Bulletin**

**508C-RB-7 Arm  
Field Adjustment Procedure**



Communication  
Systems, Inc.  
40 Greenwood Lane  
Springboro, Ohio  
45066

PH: 937-743-6010  
FX: 937-743-5664

<http://www.pdiarm.com>

## Adjustment Procedure:

PDI claims proprietary right to the material disclosed herein. This manual and associated drawings are issued in confidence for engineering information only and may not be used to manufacture anything shown herein without permission from PDI to the user.



CAUTION: Do not attempt to modify this product in any way without written authorization from PDI. Unauthorized modifications will not only void the warranty, but may lead to your being liable for any resulting property damage or user injury.

### 1. LOOSEN REAR BRAKE SCREWS 1/2 TURN WITH A 5/32 ALLEN WRENCH.



### 2. MOVE ARM INTO AJUSTMENT POSITION



### 3. MAKE YOUR ADJUSTMENTS WITH A PDI-519 ADJUSTMENT TOOL



**CAUTION!** Do not remove PDI-148 safety pin or try to re-adjust arms without a mounted TV or weight.



### 4. LOCATE PDI-519 ADJUSTMENT TOOL ON THE HEX BOLT IN THE REAR OF THE ARM, TURN BOLT 9 FULL TURNS COUNTERCLOCKWISE



## 5. RE-TIGHTEN BREAK $\frac{3}{4}$ TURN AND CHECK ADJUSTMENT



## 6. IF FURTHER ADJUSTMENT IS NEEDED, REPEAT STEP 4 TURNING $\frac{1}{2}$ TURN UNTIL DESIRED RESULTS ARE ACHEIVED

**NOTE: DO NOT REPEAT THIS STEP MORE THAN 4 TIMES**

### **For More Information**

If you have questions, please contact PDI's Engineering department at 937-743-6010