

SYMPHONY

L20 / P21 specification:

Using this document:

Simply copy and paste the descriptions for the relevant kits into your project documentation. If you want some help choosing the right one, please call or email – contact details at www.safehinge.com.

As the Symphony range affects both ironmongery and doors it is recommended to insert this specification in both the L20 [Doors] and P21 [Ironmongery] sections of your project documentation.

For an overview of considerations when using the Symphony range – please contact Safehinge direct for manufacturing details.

2.4m kits are available for tall doors – please request details at info@safehinge.com.

Product options

ALUMAX AND SURECLOSE

ALUmax with L-bracket and SUREclose S87

ALUmax 54mm pivot system with L-bracket fixing and SUREclose S87 concealed transom mount door closer (single or double swing).

Product Ref: SYM60-150-S87

Product Description: ALU60 curved aluminium profile (54mm door / 2.1m length) for door edge protection that creates constant 3mm gap between door and frame throughout opening / closing cycle to eliminate self-harm risk whilst maintaining privacy, extra long pivot straps and L-bracket floor fixing (adjustable on-site) with anti-ligature washers and cover plates with anti-tamper screw fixings.

Kit also includes SUREclose (DORMA) transom-mount concealed door closer with adjustable power rating (EN1 – EN4) and closing / latching speeds. ‘Thinking’ backcheck cushions and arrests the door at 85 - 90 degrees when thrown open with abusive force whilst not impeding opening forces during normal operation.

Manufacturer: Safehinge Ltd, Level 4, Skypark 3, 14 Elliot Place, Glasgow, G3 8EP safehinge.com

To be fitted in accordance with manufacturer's instructions (available from website or on request).

NB: Please ensure you include for deeper frame head section in door lining to accommodate the transom closer – please refer to Safehinge for specific details.

Other options continued overleaf

ALUmax with L-bracket and SUREclose S80EMB

ALUmax 54mm pivot system with L-bracket fixing and SUREclose S80EMB electro-magnetic hold open concealed transom mount door closer (single or double swing).

Product Ref: SYM60-150-S80EMB-X

(NB: X should be replaced with EN power rating 4 or 5 based on door size / weight)

Product Description: ALU60 curved aluminium profile (54mm door / 2.1m length) for door edge protection that creates constant 3mm gap between door and frame throughout opening / closing cycle to eliminate self-harm risk whilst maintaining privacy, extra long pivot straps and L-bracket floor fixing (adjustable on-site) with anti-ligature washers and cover plates with anti-tamper screw fixings.

Kit also includes SUREclose (DORMA) transom-mount concealed door closer with fixed power rating of EN4 or EN5 and adjustable closing / latching speeds. 'Thinking' backcheck cushions and arrests the door at 85 - 90 degrees when thrown open with abusive force whilst not impeding opening forces during normal operation. Electric-magnetic multi-point hold open from 75 degrees to 110 degrees, requires 24V DC power.

Manufacturer: Safehinge Ltd, Level 4, Skypark 3, 14 Elliot Place, Glasgow, G3 8EP safehinge.com

To be fitted in accordance with manufacturer's instructions (available from website or on request).

NB: Please ensure you include for deeper frame head section in door lining to accommodate the transom closer – please refer to Safehinge for specific details.

MOVASTOP

MOVASTOP removable door stop

Full length discreet removable doorstop that is easily installed and quickly removed when access is needed.

Product Ref: MOVA-2050

(NB: X should be replaced with EN power rating 4 or 5 based on door size / weight)

Product Description: Full length (2050mm) removable door stop providing maximum privacy to room occupants whilst providing emergency access using concealed anti-tamper locking lever when required. Non-handed to ensure ease of ordering and installation on door frame. Requires 40mm of space on door frame to install.

Range of finishes available – please enquire for standard / special options.

Manufacturer: Safehinge Ltd, Level 4, Skypark 3, 14 Elliot Place, Glasgow, G3 8EP safehinge.com

To be fitted in accordance with manufacturer's instructions (available from website or on request).