

# GSM Mobile Security Handset

## felsenmeer gsm s gps



Scale 1:1

### GSM voice communication and personal security inside one unit

- Mobile phone with 3 direct call buttons
- Locating with GPS
- Big red and easy identifiable emergency button
- In case of alarms speech connection and text message (SMS)
- Acoustic locating via 80 dB SPL speaker
- Entry of individual way points
- Locating via SMS or internet
- SMS maintenance
- Robust industrial housing
- Protection class IP 52 (dust and humidity protection)
- Weight 110 g

### Manual Alarm

- Panic alarm

### Automatic Alarms

- Tilt alarm
- No-motion alarm
- Time alarm
- Acoustic pre-alarm
- Zone surveillance

### Security Features

- Individual alarms settings

## Technical Data

gsm s gps		
Dimensions	135 mm x 44 mm x 25 mm	
Weight	110 g	
Protection class	IP 52	Dust and Humidity Protection
Capacity	4 phone numbers 1000 way points 10 zones	
Temperature range	Operation: Charging: Storage:	-10°C ... +55°C 0°C ... +45°C -25°C ... +70°C
Power supply	Internal lithium-polymer battery	Will be charged in the cradle resp.
Standby time	24-30 hours (typ.)	
Charging time	2-3 hours (max.)	
GSM	Triband 900 / 1800 / 1900 MHz 3V SIM card	
Audio	Speaker: Micro: Signal generator:	Phone and hands-free mode Omnidirectional 80 dB SPL (typ.)
Push buttons	Big buttons: Small button:	Alarm and voice control On / Off
Indicators	LED top: LED middle: LED below:	Green, GSM and GPS status Green, unit status Yellow, battery and charging status