

High security with personal emergency signal




funkwerk FC4 S

DECT™ Industrial personal emergency signal handset

Highlights:

- ▶ **4 will-dependent alarms:**
pressure (1 + 2), warning (1 + 2)
- ▶ **4 will-independent alarms:**
Position, no-motion, time and loss
- ▶ **Localisation** with inductive localisation transmitters (fine) and DECT base stations (rough)
- ▶ **Warden control function** with IOS display
- ▶ **Explosion protection:** gas zone 1, dust zone 11, IP65
- ▶ **Colour display** with 65,536 colours, shatterproof integration
- ▶ **Illuminated keys** with coloured menu hotkeys
- ▶ **20 MIDI ring tones** and **8 signal tones**
Volume up to 92 dB
- ▶ **Individual signalling** for internal, external and message (tone type, volume, duration, vibration)
- ▶ **Hotkey for local telephone directory** with 500 entries and temporary **muting**
- ▶ **Self-replaceable, screw-on Li-Ion-battery** with exact level indicator
- ▶ **Loudspeaker** for handsfree talking



funkwerk FC4S

DECT™ Industrie-PNA-Handset

With the new funkwerk FC4S Ex handset, Funkwerk Security Communications introduces the next generation of robust industrial personal emergency signal handsets with integrated voice and data communication, based on DECT™.

The alarm sensors can be freely parameterised for all applications and, along with the highly accurate IOS localisation, enable taking well-aimed rescue action quickly in emergencies. The loud signalling allows finding persons even in industrial environments and the automatic handsfree talking function enables calming down victims.

The high-resolution, illuminated colour display, the newly designed symbol-based user interface and the keys including coloured menu keys which are also illuminated make operating the FC4 extremely easy and a pleasure.

The battery can be changed by the user and offers state-of-the-art power management; the manifold configuration options for operation and signalling, messaging functions as well as extensive call lists make the FC4 series handsets extremely ergonomic, thus adding safety for operation and information.

^{*)} Without clip 24 mm

^{**)} With/without idle display illumination

^{***)} Depending on the selected ring tone, therefore also suited for loud environments



BG-Zertifizierung

(techn. Prüfung pos. abgeschlossen)



Funkwerk Security Communications GmbH
John-F.-Kennedy-Str. 43-53
D-38228 Salzgitter

Telefon: +49-1805 - 66 99 92*

Telefax: +49-5341 - 2235-709

www.funkwerk-sc.com

Technische Daten DECT™-PNA-Handset funkwerk FC4S

Dimensions	(LxWxH in mm)	approx. 168 x 47 x 35 mm*
	Weight (with battery)	approx. 150 g
Degrees of protection and temperature ranges	IP degree of protection:	IP65 (jet-proof and dust-tight)
	Operating temperature range:	Operation: -10... +55 °C
Power supply:	Li-Ion-replaceable-battery	3.7 V / 650 mAh (screw-on)
	Charge time:	approx. 5 hours
Battery service life	Standby:	25 - 100 hours **
	Continuous conversation:	10 - 15 hours **
DECT™ HF:	Frequency range:	1.88 ... 1.9 GHz
	Transmit power	Mean value 1 mW Peak value 250mW
Acoustic:	Acoustic signalling:	80 – 92 dB SPL*** at a distance of 30 m
	Loudspeaker:	at the rear
	Handsfree talking:	very good voice quality
	Vibration alarm:	additional or muted signalling
BG certification acc. to.:	BGR139 / VDE V 0825/1	currently in BG certification process

Accessories for funkwerk FC4S Ex

Chargers and batteries	Single charger DC4 S/Ex standard plus plug-in power supply unit
	Single charger DC4 S/Ex plus (with second battery charging) plus plug-in power supply unit
	Replaceable battery
Bags	Leather bag, quiver with a belt loop
	Protective bag, closed with window
Software	Mem-Card-Tool for Windows 2000, 2003, XP und Vista including USB card reader