



PYROTENAX MI SHEATH BONDING AND GROUNDING

The following tables present sheath resistance data for Pyrotенax System 1850 MI cables. Resistance values are given in ohms per thousand feet at 25°C (77°F). The last column in each table lists the equivalent grounding conductor size based on the sheath resistance.

Both the Canadian Electrical Code (Rule 10-804) and the National Electrical Code (Section 250.118(9) and Section 332.108) allow the sheath of copper sheathed mineral insulated cables to be employed as an equipment grounding conductor.

TABLE 1 SINGLE CONDUCTOR CABLE

Cable reference	Conductor size (AWG/kcmil)	Nominal sheath resistance (ohms per 1000 ft)	Equivalent grounding conductor size (AWG)
1/14-230	14	0.706	10
1/12-246	12	0.618	8
1/10-277	10	0.562	8
1/8-298	8	0.438	8
1/6-340	6	0.355	6
1/4-402	4	0.222	4
1/3-449	3	0.179	3
1/2-449	2	0.171	3
1/1-496	1	0.147	2
1/1/0-512	1/0	0.149	2
1/2/0-580	2/0	0.117	1
1/3/0-621	3/0	0.093	1/0
1/4/0-684	4/0	0.103	1/0
1/250-746	250	0.087	1/0
1/350-834	350	0.102	1/0
1/500-1000	500	0.073	2/0

TABLE 2 TWO CONDUCTOR CABLE

Cable reference	Conductor size (AWG)	Nominal sheath resistance (ohms per 1000 ft)	Equivalent grounding conductor size (AWG)
2/14-371	14	0.327	6
2/12-402	12	0.247	4
2/10-449	10	0.242	4
2/8-512	8	0.188	3
2/6-590	6	0.142	2
2/4-684	4	0.116	1
2/3-768	3	0.092	1/0
2/2-865	2	0.071	2/0
2/1-975	1	0.057	3/0

TABLE 3 THREE CONDUCTOR CABLE

Cable reference	Conductor size (AWG)	Nominal sheath resistance (ohms per 1000 ft)	Equivalent grounding conductor size (AWG)
3/14-387	14	0.231	4
3/12-480	12	0.140	2
3/10-480	10	0.140	2
3/8-590	8	0.104	1/0
3/6-621	6	0.102	1/0
3/4-746	4	0.071	2/0
3/3-834	3	0.057	3/0

TABLE 4 FOUR CONDUCTOR CABLE

Cable reference	Conductor size (AWG)	Nominal sheath resistance (ohms per 1000 ft)	Equivalent grounding conductor size (AWG)
4/14-465	14	0.155	2
4/12-465	12	0.217	4
4/10-590	10	0.117	1
4/8-590	8	0.117	1
4/6-730	6	0.075	2/0

TABLE 5 SEVEN CONDUCTOR CABLE

Cable reference	Conductor size (AWG)	Nominal sheath resistance (ohms per 1000 ft)	Equivalent grounding conductor size (AWG)
7/14-496	14	0.168	2
7/12-543	12	0.123	1
7/10-621	10	0.102	1/0
7/8-710	8	0.075	2/0



WWW.PENTAIRTHERMAL.COM

NORTH AMERICA

Tel: +1.800.545.6258
Fax: +1.800.527.5703
Tel: +1.650.216.1526
Fax: +1.650.474.7711
thermal.info@pentair.com

EUROPE, MIDDLE EAST, AFRICA

Tel: +32.16.213.511
Fax: +32.16.213.603
thermal.info@pentair.com

ASIA PACIFIC

Tel: +86.21.2412.1688
Fax: +86.21.5426.2917
cn.thermal.info@pentair.com

LATIN AMERICA

Tel: +1.713.868.4800
Fax: +1.713.868.2333
thermal.info@pentair.com

Pentair and Pyrotenax are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

© 2004-2013 Pentair.