



regoUniversity 2018

GEL Scripts | Intermediate

Your Guide: James Gille and Ben Rimmasch

Introductions

- Take 5 Minutes
- Turn to a Person Near You
- Introduce Yourself
- Business Cards



Agenda

- XML Manipulation
- SOAP Web Services (XOG)
- Email
- Best Practices
- Exercise

XML Manipulation

*rego*University 2018

Let Rego be your guide.

XML Manipulation – Create XML Document

- **<gel:parse>** Used to create an XML document in memory. The tag can be used to generate an entire XML document, or specific nodes that can later be attached into an existing XML document.

```
<gel:parse var="userXML">
  <NikuDataBus xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="../xsd/nikuxog_user.xsd">
    <Header action="write" externalSource="NIKU" objectType="user" version="13.2.0.472"/>
    <Users>
      <User externalId=" " isLDAP="false" uiThemeDefaultPartitionCode="" userLanguage="English" userLocale="en_US"
        userName="{row.userName}" userStatus="{row.userStatus}" userTimezone="America/Los_Angeles" userType="INTERNAL">
        <PersonalInformation emailAddress="{row.email}" firstName="{row.firstName}" lastName="{row.lastName}"/>
        <Resource resourceId="{row.resourceId}"/>
        <Groups>
          <Group id="{row.groupId}"/>
        </Groups>
      </User>
    </Users>
  </NikuDataBus>
</gel:parse>
```

XML Manipulation – Read XML Node

- **<gel:set>** Used to retrieve content of an XML node or document to a variable. This tag can also be used to change content or add elements.
 - Variable created which contains the text content of a node
`<gel:set asString="true" select="$userXML/NikuDataBus/Users/User/text()" var="textContent"/>`
 - Variable created which contains the value of a specified attribute (User Name)
`<gel:set asString="true" select="$userXML/NikuDataBus/Users/User/@userName" var="userName"/>`
 - Variable created which contains the Groups node, including all sub-nodes
`<gel:set asString="true" select="$userXML/NikuDataBus/Users/User/Groups" var="userGroups"/>`
- **<gel:expr>** Used to evaluate an expression as text
 - Logging User XML to process logs:
`<gel:log level="WARN"><gel:expr select="$userXML"/></gel:log>`
- **<gel:serialize>** Used to save the XML document
`<gel:serialize fileName="/fs0/clarity1/share/userInput.xml" var="{userXML}"/>`

XML Manipulation – Update XML Node

- **<gel:set>** This tag can also be used to change content or add elements.
 - Updates the text content of a node to the value specified
`<gel:set asString="true" select="$userXML/NikuDataBus/Users/User/text()" value="New Text"/>`
 - Updates the value of an attribute (User Name) to the specified value (jsmith)
`<gel:set asString="true" select="$userXML/NikuDataBus/Users/User/@userName" value="jsmith"/>`
 - Creates an XML node for a group and inserts it into the existing userXML document under the Groups node
`<gel:parse var="groupXML">
 <Group id="{groupRow.groupCode}"/>
</gel:parse>
<gel:set insert="true" value="{groupXML}" select="$userXML/NikuDataBus/Users/User/Groups"/>`

XML Manipulation – Delete Nodes

- Delete Node

- The following can be used to delete a group node from userXML

```
<gel:set select="$userXML//Users/User/Groups/Group[@id='pm']"  
var="groupToDelete"/>
```

```
<core:set value="{groupToDelete.getParentNode()}" var="parent"/>
```

```
<core:set value="{parent.removeChild(groupToDelete)}" var="void"/>
```


SOAP Web Services (XOG)

*rego*University 2018

Let Rego be your guide.

SOAP Web Services (XOG) – Namespaces

- Think of XML namespaces as a way to organize tag names (and attribute names) into groups
- The namespaces below are required to call CA PPM SOAP Web Services (XOG)

```
<gel:script xmlns:core="jelly:core"  
  xmlns:gel="jelly:com.niku.union.gel.GELTagLibrary"  
  xmlns:xog="http://www.niku.com/xog"  
  xmlns:soap="jelly:com.niku.union.gel.SOAPTagLibrary"  
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
```

SOAP Web Services (XOG) – Obtain Session ID

- The following snippet shows the recommended way to retrieve a session ID. This approach cannot be used for cross-environment SOAP calls.

```
<!-- Get sessionId by username -->
<gel:parameter var="username" default="admin"/>
<core:new className="com.niku.union.security.DefaultSecurityIdentifier" var="secl" />
<core:invokeStatic var="userSessionCtrl" className="com.niku.union.security.UserSessionControllerFactory" method="getInstance" />
<core:set var="secl" value="{userSessionCtrl.init(username, secl)}/>
<core:set var="sessionId" value="{secl.getSessionId()}/>

<core:choose>
  <core:when test="{sessionId == null}">
    <gel:log level="ERROR"> Unable to obtain a Session ID. </gel:log>
  </core:when>
  <core:otherwise>
    <!-- Execute XOG -->
  </core:otherwise>
</core:choose>
```

SOAP Web Services (XOG) – Build XML

- Use the <gel:parse> tag to build a XOG input XML

```
<gel:parse var="userXML">
  <NikuDataBus xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:noNamespaceSchemaLocation="../xsd/nikuxog_user.xsd">
    <Header action="write" externalSource="NIKU" objectType="user" version="13.3.0.286"/>
    <Users>
      <User externalId="" isLDAP="false" uiThemeDefaultPartitionCode="" userLanguage="English"
        userLocale="en_US" userName="{row.userName}" userStatus="{row.userStatus}"
        userTimezone="America/Los_Angeles" userType="INTERNAL">
        <PersonalInformation emailAddress="{row.email}" firstName="{row.firstName}" lastName="{row.lastName}"/>
        <Resource resourceId="{row.resourceId}"/>
        <Groups/>
      </User>
    </Users>
  </NikuDataBus>
</gel:parse>
```

SOAP Web Services (XOG) – Execute XOG

- Use the below snippet to execute a XOG SOAP web service call

```
<!-- Execute XOG -->
<soap:invoke endpoint="internal" var="result">
  <soap:message>
    <soapenv:Envelope>
      <soapenv:Header>
        <xog:Auth>
          <xog:SessionID>${sessionID}</xog:SessionID>
        </xog:Auth>
      </soapenv:Header>
      <soapenv:Body>
        <gel:include select="$userXML"/>
      </soapenv:Body>
    </soapenv:Envelope>
  </soap:message>
</soap:invoke>
```


SOAP Web Services (XOG) – Execute XOG

- Obtaining XOG endpoint

- endpoint="internal"
 - Quick way to set up SOAP call to the same instance

```
<!-- Execute XOG -->  
<soap:invoke endpoint="internal" var="result">  
  ...  
  ...  
</soap:invoke>
```

- From properties.xml using JAVA Classes

```
<core:invokeStatic className="com.niku.union.config.ConfigurationManager" method="getInstance" var="config"/>  
<core:set var="URL" value="{config.getProperties().getWebServer().getWebServerInstance(0).getSslEntryUrl()}" />  
<gel:log level="INFO">Environment is: {URL}</gel:log>
```

SOAP Web Services (XOG) – Execute XOG

- Obtaining XOG endpoint

- From properties.xml using GEL tags

- If the entryUrl doesn't work, the sslEntryUrl or schedulerUrl can be pulled

```
<core:invokeStatic className="java.lang.System" method="getenv" var="nikuHome">
  <core:arg value="NIKU_HOME"/>
</core:invokeStatic>
<gel:parse file="{nikuHome}/config/properties.xml" var="propertiesXML"/>
<gel:set asString="true"
  select="$propertiesXML/properties/webServer/webServerInstance[@id='app']/@entryUrl"
  var="host_url"/>
<gel:log level="INFO">Host URL: {hostUrl}</gel:log>
<gel:log>{hostUrl}/niku/xog</gel:log>
```

SOAP Web Services (XOG) – Parse Output

- To ensure success and as part of error handling the following snippet demonstrates how to parse through the XML response returned by the SOAP call to the XOG interface

```
<!-- Parse Results -->
<gel:set asString="true" select="$result//XOGOutput/Status/@state" var="XOGState"/>
<gel:set asString="true" select="$result//XOGOutput/Statistics" var="xogStats"/>
<gel:set asString="true" select="$result//XOGOutput/Statistics/@failureRecords" var="XOGFailures"/>

<core:choose>
  <!-- Success -->
  <core:when test="{XOGState == 'SUCCESS' and XOGFailures == 0}">
    <gel:log level="INFO">User XOG Stats: ${xogStats} </gel:log>
  </core:when>
  <!-- Failure -->
  <core:otherwise>
    <gel:log level="INFO">User XOG Stats: ${xogStats} </gel:log>
    <gel:log level="WARN"><gel:expr select="$userXML/" /></gel:log>
    <gel:log level="ERROR"><gel:expr select="$result/" /></gel:log>
  </core:otherwise>
</core:choose>
```

SOAP Web Services (XOG) – Logout

- Use the below snippet to end the XOG session

```
<!-- Logout XOG-->
<soap:invoke endpoint="internal" var="result">
  <soap:message>
    <soapenv:Envelope>
      <soapenv:Header>
        <xog:Auth>
          <xog:SessionID><![CDATA[${sessionId}]]></xog:SessionID>
        </xog:Auth>
      </soapenv:Header>
      <soapenv:Body>
        <xog:Logout/>
      </soapenv:Body>
    </soapenv:Envelope>
  </soap:message>
</soap:invoke>
```

Email

*rego*University 2018

Let Rego be your guide.

- **<gel:email>**

- Email server information is derived from the properties.xml of the installation.
- Supports HTML
- Separate multiple email addresses with a ‘;’

```
<gel:script xmlns:gel="jelly:com.niku.union.gel.GELTagLibrary">
```

```
  <gel:email from="clarity-do-not-reply@ca.com" subject="Clarity - Test Email" to="john@gmail.com">
```

```
    <![CDATA[
```

```
      This is a test email.
```

```
      <br/><br/>-----<br/>
```

```
      This is an automated message, please do not reply.
```

```
    ]]>
```

```
  </gel:email>
```

```
</gel:script>
```


- **<email:email>**

- Mail Server must be specified within the tag
- Does not support HTML
- Supports Attachments

```
<gel:script xmlns:core="jelly:core" xmlns:email="jelly:email">
```

```
  <core:invokeStatic className="java.lang.System" method="getenv" var="NIKU_HOME">
```

```
    <core:arg value="NIKU_HOME"/>
```

```
  </core:invokeStatic>
```

```
  <gel:parse file="${NIKU_HOME}/config/properties.xml" var="properties"/>
```

```
  <gel:set asString="true" select="$properties/properties/mailServer/@host" var="mailServer"/>
```

```
  <email:email to="john@gmail.com" from="clarity-do-not-reply@ca.com" subject="app-ca.log file" server="${mailServer}"  
    attach="${NIKU_HOME}/logs/app-ca.log">
```

```
    App-ca.log File
```

```
  </email:email>
```

```
</gel:script>
```

Best Practices

*rego*University 2018

Let Rego be your guide.

Best Practices

- When possible, pull server info from properties file on server
- Avoid sending emails in non-prod environments by either disabling mail server or masking emails
- GEL XML tags typically load the entire XML document into memory. Use caution when dealing with large XML files.

Exercise

*rego*University 2018

Let Rego be your guide.

Exercise

- Write a script that will email a security group a list of all projects that have inactive project managers.

Group▲		ID	Description	Status
Rego U - GEL Script Group		regou_gel_script	This group is to be used in the Rego U GEL Script Class for Exercise 2	Active

Exercise – SQL Hints

- **SQL to get Resources in Group:**

```
SELECT  r.first_name || ' ' || r.last_name resName,  
        r.email resEmail  
FROM    cmn_sec_user_groups ug  
        JOIN cmn_sec_groups g ON ug.group_id = g.id AND g.group_code = 'regou_gel_script'  
        JOIN srm_resources r ON r.user_id = ug.user_id
```

- **SQL to get Projects:**

```
SELECT  i.id prjId,  
        i.code prjCode,  
        i.name prjName,  
        r.full_name prjMgr  
FROM    inv_investments I  
        JOIN inv_projects ip ON ip.prid = i.id AND ip.is_template = 0 AND ip.is_program = 0 AND (i.purge_flag = 0 OR i.purge_flag IS NULL)  
        JOIN odf_ca_project ocp ON i.id = ocp.id  
        JOIN cmn_sec_users u ON i.manager_id = u.id AND u.user_status_id != 200  
        JOIN srm_resources r ON u.id = r.user_id
```

Questions?



*rego*University 2018

Let Rego be your guide.

Thank You For Attending regoUniversity

Instructions for PMI credits

- Access your account at pmi.org
- Click on **Certifications**
- Click on **Maintain My Certification**
- Click on **Visit CCR's** button under the **Report PDU's**
- Click on **Report PDU's**
- Click on **Course or Training**
- Class Name = **regoUniversity**
- Course Number = **Session Number**
- Date Started = **Today's Date**
- Date Completed = **Today's Date**
- Hours Completed = **1 PDU per hour of class time**
- Training classes = **Technical**
- Click on **I agree** and **Submit**



Let us know how we can improve!
Don't forget to fill out the class survey.



Phone

888.813.0444



Email

info@regouniversity.com



Website

www.regouniversity.com