



**TransTank<sup>®</sup>**  
International

The Safest Tanks in Motion

Product Specification Sheet

## DIESEL TRANSFER UNITS

### DieselCaptain<sup>™</sup> 200L

with 40L/min Dieselflo Pump and 4m x 3/4" Hose

CODE: DUL0200ALD040V1

The Internationally Certified DieselCaptain<sup>™</sup> is your ultimate and reliable refueling partner! This poly diesel fuel tank is equipped with world class pumps, hoses and auto shut off nozzles, so you can be assured your diesel refueling is done quickly and efficiently.



- » Diesel grade polyethylene - meets International Regulation ECE R34.01 requirements, & complies with AS1940-2004 and AS2809.2-2008 High unit with space saving design
- » 12 Volt 40L/min Dieselflo pump
- » 3/4" auto shut-off nozzle
- » Strong poly lid to protect pump compartment
- » Locking latch for lid, to protect your investment
- » Ergonomic lifting handles for ease of transport
- » 4m x 3/4" hose for extra reach
- » 3/4" drain bung
- » Moulded with our unique aluminium ring for incredible strength, this multi seal system keeps the rain out, and your diesel in

#### SPECIFICATIONS

Tank Material	<b>Polyethylene</b>
Lid Diameter	<b>N / A</b>
Capacity (brim full)	<b>200 Litres</b>
Tare Weight	<b>35 kg</b>
(W) Full of Water	<b>N / A</b>
Dimensions (L W H)	<b>800 x 680 x 710 mm</b>
Tank Warranty	<b>15 Years</b>
Pump Warranty	<b>1 Year</b>

[www.tti.com.au](http://www.tti.com.au)

**1800 816 277**