



TransTank[®]
International

The Safest Tanks in Motion

Product Specification Sheet

3-POINT LINKAGE SPRAYERS

LinkOn[™] Plus 1000L

with 75L/min Pump, Main Electric On/Off, and In-Cab Switch Box

CODE: PLG1000L0750-12

Hook up and go with TTI's LinkOn[™] Sprayer Range. From small acreage farms to large scale operations, TTI's range of 3 point linkage boom sprayers are the perfect choice to get your boom spraying done on time using your tractor.

- » UV Stabilised tank, no risk of going brittle in the sun!
- » Fully drainable tank with sump, ideal for cleaning and ensuring there is no residue
- » Built in 10L fresh water tank with tap
- » Hot dipped galvanised steel frame. No rust or fading
- » Engineer approved frame
- » Forklift pockets for ease of handling
- » 455mm hinge type lid with basket filter. Easy access for cleaning and filling
- » 75L/m Bertolini (Italian) diaphragm pump. 218psi (15Bar) pressure.
- » Arag 3-way pressure regulator and gauge, main electric on/off, in-cab switch box
- » Quality filtration system to protect the pump
- » PTO shaft with protection covers
- » 12m galvanized steel boom with breakaway & self-leveling kit, complete with non drip nozzles



SPECIFICATIONS

Tank Material	Polyethylene
Lid Diameter	250 mm/455 mm
Capacity (brim full)	1000 Litres
Tare Weight	250 kg
(W) Full of Water	N / A
Dimensions (LWH)	N / A
Tank Warranty	20 Years
Frame Warranty	5 Years
Pump Warranty	2 Years

www.tti.com.au

1800 816 277