

OXFORD
LAB PRODUCTS

BenchMate® E

Electronic Pipette



Transformative Pipetting

Available at

Pipette.com

info@pipette.com • 800-243-3232

Oxford Lab Products
BenchMate® E Electronic Pipette
Features and Benefits

Easy to Use

Simple, color interface to quickly choose pipetting mode



Ergonomic Design

Ultra lightweight, balanced to reduce RSI

One Click Favorites

Store and recall up to 3 frequently used programs

Popular Pipetting Modes



Smart Charging

Pipette can be used while plugged in. Battery charges in 2 hours when pipette is not in use.

Password Protected

Secures calibration due date

Robust

Stepper motor for accurate, precise, and reliable pipetting

Lifetime Warranty*

Durable equipment built to last

*Lifetime warranty only available in the Continental USA



Oxford Lab Products

BenchMate® E Electronic Pipette

Product Overview



Intuitive Display

Easy-to-Use Buttons

Ergonomically Balanced
Finger Hook






Lower Assembly is
Autoclavable

Computer Controlled
Aspirating and Dispensing






Universal Tip Cones

Specially Designed Tip Cones with
O-rings for Leak-free Pipetting

Single Channel BenchMate® E Electronic Pipettes

| Single Channel Catalog No. | Volume Range (µL) | Increments (µL) | Volume (µL) | Accuracy (systematic error) AC (%) | Precision (random error) CV (%) |
|----------------------------|--|-----------------|---------------------|------------------------------------|---------------------------------|
| OBE-10 | 0.5 to 10  | 0.01 | 1 5 10 | ±2.5 ±2 ±1 | ≤1.8 ≤1 ≤0.6 |
| OBE-100 | 5 to 100  | 0.1 | 10 50 100 | ±3 ±1 ±0.8 | ≤1 ≤0.5 ≤0.2 |
| OBE-200 | 10 to 200  | 0.1 | 20 100 200 | ±2.5 ±0.7 ±0.6 | ≤0.7 ≤0.3 ≤0.2 |
| OBE-1000 | 50 to 1000  | 1 | 100 500 1000 | ±3 ±1 ±0.6 | ≤0.6 ≤0.4 ≤0.2 |
| OBE-5000 | 250 to 5000  | 5 | 500 2500 5000 | ±2.4 ±1.2 ±0.6 | ≤0.6 ≤0.25 ≤0.15 |

Multichannel BenchMate® E Electronic Pipettes

| 8-Channel Catalog No. | 12-Channel Catalog No. | Volume Range (µL) | Increments (µL) | Volume (µL) | Accuracy (systematic error) AC (%) | Precision (random error) CV (%) |
|-----------------------|------------------------|--|-----------------|------------------|------------------------------------|---------------------------------|
| OBE8-10 | OBE12-10 | 0.5 to 10  | 0.01 | 1 5 10 | ±8 ±4 ±2 | ≤5 ≤2 ≤1 |
| OBE8-20 | OBE12-20 | 2 to 20  | 0.01 | 2 10 20 | ±7 ±3 ±2 | ≤3 ≤2 ≤1.6 |
| OBE8-100 | OBE12-100 | 5 to 200  | 0.1 | 10 50 100 | ±3 ±1 ±0.8 | ≤2 ≤0.8 ≤0.3 |
| OBE8-200 | OBE12-200 | 10 to 200  | 0.1 | 20 100 200 | ±5 ±1 ±0.7 | ≤1.4 ≤0.4 ≤0.25 |
| OBE8-300 | OBE12-300 | 15 to 300  | 0.1 | 30 150 300 | ±3 ±1 ±0.6 | ≤1 ≤0.5 ≤0.3 |



Pipette Stands for BenchMate® E Electronic Pipette

| Catalog No. | Description |
|-------------|---|
| OBE-S | Acrylic Pipette Stand, for One Pipette |
| OBE-CS | Charging Pipette Stand, for One Pipette |

