

ENHANCED DIRECTORY SETTINGS

CSV DIRECTORY SETTINGS

PARAMETER – <i>directory 1</i>	CONFIGURATION FILES
DESCRIPTION	<p>startup.cfg, <model>.cfg, <mac>.cfg</p> <p>The name of the first CSV-based directory list file that you can download from the configuration server.</p> <p>You can use this parameter in three ways:</p> <ul style="list-style-type: none"> • To download no directory • To download a directory from the original configuration server • To download a directory from another specified server <p>To download a specific file, the string value MUST HAVE A FILENAME at the end of the string. For example:</p> <ul style="list-style-type: none"> • directory 1: tftp://10.30.102.158/path/companylist.csv <p>where “path” is the directory and “companylist.csv” is the filename. If you do not specify a filename, the download fails.</p> <p>See examples for each below.</p>
FORMAT	Alphanumeric characters
DEFAULT VALUE	N/A
RANGE	N/A
EXAMPLE	<p>Example The following example downloads no directory:</p> <ul style="list-style-type: none"> • directory 1: <p>The following example downloads a company directory from the original configuration server:</p> <ul style="list-style-type: none"> • directory 1: companylist.csv <p>The following example downloads a company directory file from the specified server in the “path” directory:</p> <ul style="list-style-type: none"> • directory 1: tftp://192.168.0.55/path/companylist.csv

PARAMETER –
directory 2

CONFIGURATION FILES

startup.cfg, <model>.cfg, <mac>.cfg

DESCRIPTION

The name of the second CSV-based directory list file that you can download from the configuration server.

You can use this parameter in three ways:

- To download no directory
- To download a directory from the original configuration server
- To download a directory from another specified server

To download a specific file, the string value **MUST HAVE A FILENAME** at the end of the string. For example:

- directory 1: tftp://10.30.102.158/path/companylist.csv

where “path” is the directory and “companylist.csv” is the filename. If you do not specify a filename, the download fails.

See examples for each below.

FORMAT

Alphanumeric characters

DEFAULT VALUE

N/A

RANGE

N/A

EXAMPLE

Example The following example downloads no directory:

- directory 1:

The following example downloads a company directory from the original configuration server:

- directory 1: companylist.csv

The following example downloads a company directory file from the specified server in the “path” directory:

- directory 1: tftp://192.168.0.55/path/companylist.csv

PARAMETER – <i>directory 1 name</i>	CONFIGURATION FILES startup.cfg, <model>.cfg, <mac>.cfg
DESCRIPTION	Specifies the folder name of the directory defined in the “directory 1” parameter.
FORMAT	Alphanumeric characters
DEFAULT VALUE	Corporate
RANGE	N/A
EXAMPLE	directory 1 name: Office

PARAMETER – <i>directory 2 name</i>	CONFIGURATION FILES startup.cfg, <model>.cfg, <mac>.cfg
DESCRIPTION	Specifies the folder name of the directory defined in the “directory 2” parameter.
FORMAT	Alphanumeric characters
DEFAULT VALUE	Personal
RANGE	N/A
EXAMPLE	directory 1 name: Friends

PARAMETER – directory 1 enabled	CONFIGURATION FILES startup.cfg, <model>.cfg, <mac>.cfg
DESCRIPTION	Specifies whether or not the directory defined in the “directory 1” parameter should be enabled to be accessed on the phone.
FORMAT	Boolean
DEFAULT VALUE	1 (Enabled)
RANGE	0 (Disabled) 1 (Enabled)
EXAMPLE	directory 1 enabled: 1