



Excellent interactive touch display with fast & accurate V-Sense touch technology. i3 offers an exciting, easy to use and affordable alternative to traditional interactive board solutions. The i3TOUCH E series provides crystal clear, high-definition images. The V-Sense 20-point touch technology operates at the touch of a finger or pen and reacts instantly.

# Top features



### Annotation overlay

Annotate over any image, site, app and save your notes in i3NOTES.



### Plug & play

Slide an OPS computer into the display and get started immediately.



### 20 touch points

The integrated multi-touch technology recognises up to 20 touch points at the same time.



### **Simple Notetaking**

Open the easy to use whiteboarding app to take notes and share immediately.

WARRANT

### Accessories



Penholder (optional)



2 passive styli

# Software options



### Android™ platform

The Android OS has built-in apps such as a web browser, file explorer and documents editor. Browse the internet and open your MS Office or PDF files without needing a computer.



# No maintenance worries - up to 8 years warranty

At i3-Technologies, we are proud of our quality products and we offer a warranty of up to 8\* years, which is unique in the market.



# Advanced infrared technology

The touchscreen gives perfect results when working in strong light, thanks to the V-Sense touch technology.



### Instant presenting

Use the i3ALLSYNC mirroring app to share your screen instantly on the display.

# **Specifications**

PRODUCT INFORMATION	
Model name	i3TOUCH E1075 4K
Product series	i3TOUCH Excellence - Interactive Flat Panel Displays
Product order code	TBC
DISPLAY SPECIFICATIONS	
Display technology	Liquid Crystal Display (LCD) with DirectLED lighting
Panel active screen area	1650.0 x 927.9 mm 64.96" x 36.54"
Display aspect ratio	16:9
Display native resolution	3840 x 2160 pixels - 4K Ultra High Definition
Brightness	330 cd/m²
Contrast ratio	1200:1
Viewing angle	178° / 178°
Colour depth	1.073 billion colors (10 bit)
Response time (typ.)	8 ms
Refresh rate	60 Hz (@ UHD)
Pixel pitch	0.372 x 0.372 mm
Supported orientation	Landscape
Glass	4 mm Hardened Anti-Reflection Safety Glass
Life time	30,000 hours
CONNECTIVITY	
Digital audio-video inputs	2x HDMI 2.0
Digital audio-video output	1x HDMI 2.0
Analogue audio-video input	1x VGA (DE-15 male) + audio jack (3.5 mm TRS connector)
Analogue video output	1x AV (TRRS connector)
Analogue audio output	1x audio jack (TRS connector)
Digital audio output	1x digital coax (RCA connector)
USB data ports	2x USB 3.0
	2x USB 2.0
Integrated PC slot	OPS-PC slot (JAE TX24 connector)
Control input	1x COM DE-9 (RS-232 standard)
Network	LAN: RJ-45 connector (100 Mbit/sec)
	Wi-Fi: 2.4 / 5 GHz (802.11 a/b/g/n/ac)
	Bluetooth: 4.0
Integrated loudspeakers	2 x 12 Watt

OPERATIONAL FEATURES		
	A color day 7.0	
Operating System	Android™ 7.0	
Architecture	CPU: ARM CORTEX Dual Core A73 (2.8 GHz)	
	GPU: ARM MALI-450	
	RAM: 2 GB	
	ROM: 16 GB	
Interactive touch	Technology: V-Sense Infrared Touch recognition	
	Input Detection: 20 touch inputs	
	Touch Connection: 1x USB-B	
	Recognition: Finger or passive stylus (size ≥ 3 mm)	
	Response time: < 4 ms (regular touch), < 25 ms (max touch inpu	uts)
	Accuracy: ± 1 mm	
Supported Compatibility	Windows, Android, Macintosh OS X, Linux, Chrome OS	
Maximum operating hours	18 hours / day	
Languages	English, Dutch, French, German, Danish, Polish, Czech, Swedish, Finnish, Norwegian, Spanish, Italian, Portuguese, Greek, Romanian, Russian, Arabic, Turkish, Ukrainian, Chinese (traditional), Chinese (simplified), Japanese, Korean	
PHYSICAL PROPERTIES		
Product dimensions	1763 x 1016 x 100 mm	69.41" x 40.00" x 3.94"
Net product weight	58 kg	22 A 10100 A 3.3 I
Packaging Size	1915 x 1125 x 280 mm	75.4" × 44.3" × 11.1"
Packaged Weight	76 kg	, 5. T. A TT. J. A   11.1
	800 x 400	
Mounting Pattern		
Color	Black front bezel, black back cabinet	
WARRANTY		
Standard warranty	5 years	
Extended warranty (optional)	for education entities: 8 years (via registration)	
	for corporate entities: 8 years (available for purchase)	
ACCESSORIES		
Included	User Manual	
	Remote Control	
	Power Supply Cord	
	HDMI cable (3 meter)	
	USB cable (5 meter)	
	2x passive stylus	
	Pen Tray	
	Wall Mount	
Optional	i3FLOORSTAND series – Display stands and floorlifts	
Ориони	i3COMPUTER OPS	
DECLUATION MECANICATION	Scom of the of 3	
REGULATORY INFORMATION	CT. TCC	
Product type approval	CE, FCC	
SOFTWARE FEATURES		
i3NOTES Whiteboarding application	Make annotations and share immediately with every device.	
i3OVERLAY Screen annotation application	Write on top of every image/app/site & save your content in i3N	OTES+
i3ALLSYNC Wireless video cast application	Share you content wirelessly from any device (min: Windows 7, touch function and audio transmission on Windows & OSX. Up to follow the meeting.	
ELECTRICAL PROPERTIES		
Power voltage	100 ~ 240 Volt – 50/60 Hz	
Power consumption	322 Watt (standby < 0.5 Watt)	
ENVIRONMENTAL CONDITIONS		
Operating temperature	0° C to 40° C	
Operating temperature  Operating humidity	10% to 90% RH non-condensing	
	-20° C to 40° C	
Storage temperature Storage humidity		
	10% to 90% RH non-condensing	
Maximum operational altitude	5,000 meters	

# i3ALLSYNC REQUIREMENTS Client laptop and mobile device requirements Laptops & Tablet PCs iPads, iPhones,& iPods Android Tablets & Phones

Operating System	OSX 10.10 or newer	iOS version 7.0 or newer	or newer
Minimum Required	Intel Core i3 4th generation, 4 GB RAM	iPad 3 / iPhone 5 or newer	Phones/Tablets with Android 5.0 or newer

#### NETWORK REQUIREMENTS

Network and Internet Access

When i3ALLSYNC is deployed into the existing network, the host PC and the clients require wired or wireless network connection with a minimum bandwidth of 20 Mbps. When running HD content, increase the minimum bandwidth to 50 Mbps. Like any network application, the overall performance is dependent on available bandwidth. Internet access is also required to update the i3ALLSYNC receiver app.

#### **FUNCTIONALITY**

- Screen mirroring from any device (with minimum requirements)
- FHD resolution
- Wireless touch function on Windows & MAC OS.
- Up to 64 devices can use the remote view simultaneously to follow the meeting.
- i3ALLSYNC app available in the Apple store, Play store and on i3-allsync.com. (by the end of May 2018)
- i3ANNOTATE on all share images and save your content in i3NOTES Whiteboard

## Technical drawing







