

Giving Shape to Ideas





bizhub C558

If your workload is growing, the bizhub C558 is the MFP solution you've been searching for - with 55 ppm print/copy output in superior Simitri HD color or cost-effective B&W. The C558 also offers standard dual scanning at up to 240 opm, 6,650-sheet maximum paper capacity, enhanced touch-and-swipe operation on the large 10.1 inch control panel and full solution integration.

System Overview

System memory	4 GB		
System hard disk	250 GB Standard		
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0		
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS		
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP		
Dual scan document feeder	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm		
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper max: 11.75" x 47.25"		
Printable paper weight	52-300 gsm		
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets		
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm		
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm		
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm		
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm		
Large capacity tray LU-207 (optional)	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm		
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm		
Large capacity tray PC-415 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm		
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm		
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm		
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, post-insertion, booklet		
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets		
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheet (up to 209 gsm)		
Stapling output capacity	Max.: 1,000 sheets		
Tri-fold (optional)	Up to 3 sheets		
Tri-fold capacity	Max.: 30 sheets (tray)		
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)		
Booklet output capacity	Max.: 100 sheets (tray)		
Copy/print volume	Max.: 200,000 pages/month ¹		
Toner lifetime	Black: 28,000 pages / CMY: 26,000 pages		
Imaging unit lifetime	Black: 145,000 pages / 600,000 pages (Drum / Developer) CMY: 130,000 pages / 600,000 pages (Drum / Developer)		
Powerconsumption	120 V / 60 Hz, less than 0.5 kW (system)		
System dimensions	24.2" x 27" x 38" (W x D x H)		
System weight	Approx. 242.5 lb		

Copying process	Electrostatic laser copy, tandem, indirect	
Tonersystem	Simitri® HD Polymerized Toner	
Print speed (8.5" x 11")	B&W / Color: up to 55 ppm (Portrait)	
Print speed (11" x 17")	B&W / Color: up to 27 ppm (Portrait)	
Autoduplex speed (8.5" x 11")	B&W / Color: up to 55 ppm (Portrait)	
1st copy out time	B&W: 4.4 sec. / Color: 3.5 sec.	
Warm-up time	Approx. 22 sec. ²	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Copy functions	ons Electronic sorting, multi-job, adjustments (contrast, sharpne image density), proof copy, interrupt mode, color mode, seps scan, sort/group, combination, original selection, ID card cop 2-in-1, 4-in-1	

Printer Specifications

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi	
PDL	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS	
Operating systems Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2³ / 20 Macintosh OS X 10.6 or later Linux / Citrix		
Printerfonts	80 PCL Latin, 137 PostScript 3	
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print	

Printer Specifications (Optional)

Print controller	Embedded Fiery IC-416 (VI-510 required)	
Memory/HDD	2 GB / 160 GB	
PDL	PostScript 3 (ver. 3019) PCL 6/5c	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.8 or later	

Scanner Specifications			
Scan speed .	B&W / Color: up to 240 ipm		
Scan resolution	Max.: 600 x 600 dpi		
Scan modes Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan		
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)		
Scan destinations	2,100 (shared with fax), LDAP support		

realtime scan preview

Fax Specifications

Scan functions

Fax	Super G3 (optional)	
Transmission	nsmission Analog, Internet fax, Color i-Fax, IP-Fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt Email/FTP/SMB, up to 400 job programs	

Annotation (text/time/date) for PDF, up to 400 job programs,

User Box

Specifications		
Storable documents	Max.: 3,000 documents or 10,000 pages Public Personal (with password or authentication) Group (with authentication)	
Type of user boxes		
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation	
Userbox functionality Reprint, combination, download, sending (Email/FTP/SI copy box-to-box		

Security	ISO 15408 EAL ⁴ IEEE 2600.1 ⁴ IP filtering dort blocking SSL2, SSL3 and TSL1.0 network communication IPsec support IEEE 802.1x support FIPS 140-2 User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax receipt, Print user data encryption Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts Active Directory support (user name + password + Email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility

I Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

2 Warm-up time may vary depending on the operating environment and usage

3 Supports x64 only

4 Certification pending

Components and Opti	ons	
AU-102 Biometric authentication	Finger vein scanner	
AU-204H Universal ID card reader	Magnetic stripe card reader: requires WT-506 Working table	
AU-205H Universal ID card reader*	Various ID card technologies	
AU-211 CAC/PIV solution	Requires WT-506 Working Table	
EK-608 USBI/F kit	USB keyboard connection	
EK-609 USBI/F kit	USB keyboard connection, Bluetooth	
DK-510 Copier desk	Provides storage space for print media and other materials	
FK-514 Fax board	Super G3 fax, digital fax functionality	
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)	
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output	
FS-536 Staple finisher	50-sheet stapling, 3,300 sheets max. output	
FS-536SD Booklet finisher	50-sheet staple finisher, 20-sheet booklet finisher, 3,300 sheets max. output	
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output	
FS-537SD Booklet finisher	100-sheet stapling, 20-sheet booklet finisher, 2,500 sheets max. output	
HD-524 Hard disk	Backup HDD	
IC-416 Fiery image controller	Embedded image controller for graphics-intensive applications	
JS-506 Job separator	Separation for fax output, etc.	
JS-602 Job separator for FS-537	Separation for fax output, etc.	
Keyboard	External keyboard (requires KH-102)	
KH-102 Keyboard holder	To place USB keyboard	
KP-101 10-Key pad	For use instead of touchscreen	
LK-102 v3 PDF enhancements	PDF/A, PDF encryption, digital signature	
LK-104 v3 Voice guidance	Provides voice guidance functions	
LK-105 v4 OCR text recognition	Searchable PDF	
LK-106 Barcode fonts	Supports native barcode printing	

LK-107 Unicode fonts	Supports native Unicode printing	
LK-108	Supports native OCR A and B font printing	
OCR A and B fonts		
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines	
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functional	
LK-111	Print data compression for reduced network impact	
ThinPrint® Client		
LU-207	8.5" x 11" to 12" x 18", 2,500 sheets / 52-256 gsm	
Large capacity unit		
LU-302	8.5" x 11", 3,000 sheets / 52-256 gsm	
Large capacity unit		
MK-730 Mount kit	Banner paper guide	
MK-735 Mount kit	Installation kit for ID card reader	
MK-742 Mount kit	Installation kit for FK-515 fax board	
OT-506 Output tray	Output tray used instead of finisher	
PC-115	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm	
Universal tray(x1)	10 P	
PC-215	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm	
Universal tray (x2)	· · · · · · · · · · · · · · · · · · ·	
PC-415	8.5" x 11", 2,500 sheets, 52-256 gsm	
Large capacity tray		
PI-507 Post inserter	Cover insertion, post finishing	
for FS-537	0.00	
PK-519 Punch kit for FS-533	2/3-hole punching, autoswitching	
	2011	
PK-520 Punch kit for FS-536	2/3-hole punching, autoswitching	
PK-523 Punch kit	2/2 halo numbhina automitabina	
for FS-537	2/3-hole punching, autoswitching	
RU-513 Relay unit	Required for FS-537/FS-537SD and FS-536/FS-536SD	
SC-508 Security kit	Copy Guard function (2x required)	
SK-602 Staple kit	Added stapling functionality kit	
SP-501 Stamp unit		
UK-212 Wireless LAN	Added fax stamp capability kit	
UK-501 Multi-feed	Wireless LAN to network connector	
detection kit	Detects multi-feeding in the document feeder	
VI-510 Interface kit for IC-416	Fiery controller interface card	
WT-506 Working table	Authentication device placement	
ZU-609 Z-fold unit for FS-537	Z-fold for 11" x 17" prints, 2/3-hole punching	

^{*} May not be available at time of launch.



Partnership.

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

Information Management	IT Services	Technology
Enterprise Content Management (ECM)	Application Services	Office Multifunction Business Solutions
Document Management	Cloud Services	Commercial and Production Printers
Automated Workflow Solutions	IT Security	3D Printers
Business Process Automation	Managed IT Services	Wide Format Printers
Security and Compliance	IT Consulting & Projects	Laptops, Desktops and Computer Hardware
Mobility		Servers and Networking Equipment
eDiscovery Services		Managed Print Services (MPS)
		Managed Enterprise Services

For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2016 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA, INC. All other product and brand names are trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com





