

SSFP-PxxMx-1 Cable Assemblies - SFP+ 10Gb/s Direct-Attach Copper

Preview Document. Not Live Data.



For more Information
please call

1-800-Belden1



Description

SFP+ to SFP+ Direct-Attach Copper, 10Gb/s, Black

Usage (Overall):

Suitable Applications

Data Centers, Main Equipment Rooms, Telecommunications Rooms, Work Area, 1-10G Ethernet, 1/2/4/8G Fiber Channel, 10G Fiber Channel over Ethernet, SDR, DDR, QDR, FDR-10 Infiniband, Storage Area Networks (SAN), Network Attached Storage (NAS) and High Performance Computing.

Cable Characteristics (Connectivity):

DAC Specs-Length

Length	# Pairs	AWG	Conductor material	Cable Type	Cable O.D.
0.5 M to 3.0 M	2	30	Solid Copper Silver Plated	Twinax	4.5 mm (0.178 in.)
>3.0 M to 7.0 M	2	24	Solid Copper Silver Plated	Twinax	6.3 mm (0.248 in.)

Insulation:

Insulation Material

Insulation Material
PO - Polyolefin

Outer Shield:

Outer Shield Material

Layer #	Outer Shield Material	Coverage (%)
1	Aluminum Foil-Polyester Tape	100.000
2	Aluminum Braid	85.000

Outer Jacket:

Outer Jacket Material

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling:

Overall Cabling Black

Physical Characteristics (Connectivity):

Materials:

Materials

Description	Material	Color
SFP+ Backshell	Nickel plated zinc alloy diecast	Bright Nickel
SFP+ Pull Tab	PVC	Black
PCB bare board	Improved FR4 UL94V-0	
PCB Contacts	Gold plated contacts	
Boot	PVC	Black

Mechanical Characteristics (Connectivity):

Footprint/Type SFP+ to SFP+

Termination Interface

Termination	Connection	Durabilities
SFP+	Mated Connection	100

Cable/Connector Retention: 38.218 lbs.

Plug/Connector Retention: 20.233 lbs.

SSFP-PxxMx-1 Cable Assemblies - SFP+ 10Gb/s Direct-Attach Copper

Insertion Force to Cage:	4.047 lbs.
Withdraw Force from Cage:	2.810 lbs.
Storage Temperature Range	-40°C To +80°C
Installation Temperature Range	0°C To +70°C
Operating Temperature Range	0°C To +70°C
Min. Bend Radius (Overall Cable):	1.250 in.
Flex Cycle Rating	100 min.

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards & Environmental Programs:

CEC/C(UL) Specification	CL2
CSA Specification	FT4
IEEE Specification	IEEE802.3
EU Directive 2002/95/EC (RoHS)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	01/01/2006
MII Order #39 (China RoHS)	Yes
Other Specification	SFF-8431 (Electrical), SFF-8432 (Mechanical)

Transmission Characteristics (Connectivity):

Electrical Characteristics (Overall):

Electrical Characteristics

Electrical Parameters	SSFP-P0M5-1	SSFP-P1M0-1	SSFP-P2M0-1	SSFP-P3M0-1	SSFP-P5M0-1	SSFP-P7M0-1
Dielectric Strength	300 v	300 v	300 v	300 v	300 v	300 v
Current Rating	0.5 A	0.5 A	0.5 A	0.5 A	0.5 A	0.5 A
Insulation Resistance	1000 M-Ohms Min.	1000 M-Ohms Min.	1000 M-Ohms Min.	1000 M-Ohms Min.	1000 M-Ohms Min.	1000 M-Ohms Min.
Contact Resistance	50 m-Ohms Max.	50 m-Ohms Max.	50 m-Ohms Max.	50 m-Ohms Max.	50 m-Ohms Max.	50 m-Ohms Max.
ESD (contacts)	1kV	1kV	1kV	1kV	1kV	1kV
ESD (direct/air discharge to module)	8KV/16kV	8KV/16kV	8KV/16kV	8KV/16kV	8KV/16kV	8KV/16kV
Impedance	90 to 110 Ohms	90 to 110 Ohms	90 to 110 Ohms	90 to 110 Ohms	90 to 110 Ohms	90 to 110 Ohms
Propagation Delay	5.2 nsec/m	5.2 nsec/m	5.2 nsec/m	5.2 nsec/m	4.5 nsec/m	4.5 nsec/m
Intra-Pair skew	15 psec/m	15 psec/m	15 psec/m	15 psec/m	15 psec/m	15 psec/m
Insertion Loss @5 GHz	2 dB	3.5 dB	7 dB	10.5 dB	10.5 dB	14.7 dB
Difference Waveform Distortion Penalty (dWDPc)	-	1.68 dB	-	3.7 dB	-	-
Voltage Modulation Amplitude Loss (L)	-	1.07 dB	-	3.5 dB	-	-
Voltage Modulation Amplitude Loss to Crosstalk Ratio (VCR)	-	38.4 dB	-	37.0 dB	-	-
AC Common-Mode Voltage (Vcm)	-	8.8 mVrms	-	9.4 mVrms	-	-
Differential-Mode Return Loss Margin (SDDxx) (0.01-4.1GHz)	-	4.0 dB	-	6.4 dB	-	-
Differential-Mode Return Loss Margin (SDDxx) (4.1-11.1GHz)	-	3.6 dB	-	3.8 dB	-	-
Common-Mode Return Loss Margin (SCCxx) (0.01-2.5GHz)	0 dB	0.1 dB	-	0.5 dB	-	-
Common-Mode Return Loss Margin (SCCxx) (2.5-11.1GHz)	1.0 dB	1.0 dB	-	1.0 dB	-	-
Common to Differential Mode conversion (SCDxx) (0.01-4.1GHz)	-	13.6 dB	-	14.5 dB	-	-
Common to Differential Mode conversion (SCDxx) (4.1-11.1GHz)	-	5.8 dB	-	5.2 dB	-	-

Notes (Overall):

Product Family:

Product List

Belden P/N	Description
SSFP-P00M5-1	DAC, SFP+ 10Gb/s 0.5M
SSFP-P01M0-1	DAC, SFP+ 10Gb/s 1M
SSFP-P02M0-1	DAC, SFP+ 10Gb/s 2M
SSFP-P03M0-1	DAC, SFP+ 10Gb/s 3M
SSFP-P05M0-1	DAC, SFP+ 10Gb/s 5M
SSFP-P07M0-1	DAC, SFP+ 10Gb/s 7M
QSFPP-P00M5-1	DAC, QSFP+ 40Gb/s 0.5M
QSFPP-P01M0-1	DAC, QSFP+ 40Gb/s 1M
QSFPP-P02M0-1	DAC, QSFP+ 40Gb/s 2M

SSFP-PxxMx-1 Cable Assemblies - SFP+ 10Gb/s Direct-Attach Copper

QSSFP-P03M0-1	DAC, QSFP+ 40Gb/s 3M
QSSFP-P05M0-1	DAC, QSFP+ 40Gb/s 5M
QSSFP-P00M5-1	DAC, QSFP+/4SFP+ 40Gb/s 0.5M
QSSFP-P01M0-1	DAC, QSFP+/4SFP+ 40Gb/s 1M
QSSFP-P02M0-1	DAC, QSFP+/4SFP+ 40Gb/s 2M
QSSFP-P03M0-1	DAC, QSFP+/4SFP+ 40Gb/s 3M
QSSFP-P05M0-1	DAC, QSFP+/4SFP+ 40Gb/s 5M

Revision Number: 0 Revision Date: 03-05-2015

© 2015 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.