

AX101448 Modular Connectors - GIGABIX CONNECTOR 25-PAIR



For more Information
please call

1-800-Belden1



General Description:

GIGABIX CONNECTOR 25-PAIR

Usage (Overall)

Suitable Applications:	IBDN System 1200, TIA Category 5E, ISO Class D, 1000 BASE-T
Related Parts:	Compatible with GigaBIX patch cord, GigaBIX termination kit, GigaBIX rack mount panel, designation strips, wire guard

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (in.)	Width (in.)	Depth (in.)
0.310	6.630	1.280

Materials

Materials:

Description	Type	Material
Front Connection	IDC	Copper Allow with Nickel Plating
Rear Connection	IDC	Copper Allow with Nickel Plating
Connector Body		Plastic - UL940V-0

Weight

Weight:	0.110 lbs.
----------------	------------

Packaging

Packaging:	packaged in carton. Standard pack of 12 units.
-------------------	--

Mechanical Characteristics (Connectivity)

Termination Interface:

Termination	Connection	Durabilities
Front	Gas Tight IDC Connection	200 terminations
Rear	Gas Tight IDC Connection	200 terminations

Storage Temperature Range:	-40°C To +70°C
Installation Temperature Range:	-10°C To +60°C
Operating Temperature Range:	-10°C To +60°C
Tool Compatibility:	BIX Connecting Tool (A0270165)

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

Other Standards:	FCC Part 68, Subpart F, IEC 60603-7
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
Telecommunications Standards:	Category 5e - TIA 568.C.2
Third Party Performance Verification:	ETL - Verified Category 6
Safety Listing:	ACA, Bi-national Standard Listed

Suitability

Suitability - Indoor:	Yes - Indoor
------------------------------	--------------

Transmission Characteristics (Connectivity)

Mated Connection Table 1:

Frequency (MHz)	Max. Insertion Loss TIA* (dB)	Max. Insertion Loss Belden** (dB)	Min. NEXT TIA* (dB)	Min. NEXT Belden** (dB)	Min. FEXT TIA* (dB)	Min. FEXT Belden** (dB)
100.000	0.200	0.160	43.000	45.800	35.100	46.800

AX101448 Modular Connectors - GIGABIX CONNECTOR 25-PAIR

Mated Connection Table - Footnote:

* IIA/EIA-568-C-2 Category 5e Standard.

Mated Connection Table 2:

Frequency (MHz)	Min. Return Loss TIA* (dB)	Min. Return Loss Belden** (dB)	Min. Balanced TCL Belden** (dB)
100.000	20.000	27.000	32.000

Dielectric Strength: 1,000 V RMS @ 60 Hz for 1 minute

Current Rating: 1,500 A

Insulation Resistance: 500 M-Ohm Minimum

Max. Contact Resistance: 1 m-Ohm

Notes (Overall)

Notes: For proper installation refer to Installation Guide PX101820 (French) or PX101821 (English) included with the product or visit our web site at <http://www.belden.com>

Notes (Cont'd.): Suitable for 22 to 26 Wire Gauge.

Product Family

Part Number List:

Description	Item Number
GigaBIX Connectors - 6 ports	AX101447
GigaBIX Connectors - 25 pairs	AX101448

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX101448	1 EA	0.222 LB			GIGABIX CONN POLARIZED 25-PAIR

Revision Number: 0 Revision Date: 08-05-2014

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.