

OSP6AU Multi-Conductor - Category 6A Outside Plant Cable



For more Information
please call

1-800-Belden1



General Description:

CAT6A (500 MHz), 4 Pair, U/UTP-Unshielded, Outdoor OSP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Patented X-Spline, Gel-Filled, Polyolefin Inner Jacket, EquiBlock™ Technology, Ripcord, UV-Resistant LLDPE Jacket

Usage (Overall)

Suitable Applications: Outside Plant, 10 Gigabit Ethernet, Wireless, Wi-Fi, 100Base TX, 100Base VG ANYLAN, 155ATM, 622ATM, HDBASET, 4K, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio AES51, RS-422, PoE, PoE Plus

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Total Number of Conductors: 8

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Separator

Separator Material: Patented X-spline Central Member

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)	Dia. (in.)
Patent Pending EquiBlock Barrier Tape	Tri-Laminate	Polyester / Foil / Polyester	100.000	0.260

Inner Jacket

Inner Jacket Material:

Layer #	Inner Jacket Material	Nom Wall (in.)	Nom. Dia. (in.)
1	Black LLDPE	0.020	0.260

Inner Jacket Ripcord: No

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Black PO - Polyolefin

Outer Jacket Diameter:

Nom. Dia. (in.)
0.355

Outer Jacket Ripcord: Yes

Pair

Pair Color Code Chart:

Number	Color
1	White/Blue
2	White/Orange
3	White/Green
4	White/Brown

Mechanical Characteristics (Overall)

Storage Temperature Range: -40°C To +75°C

Installation Temperature Range: -40°C To +60°C

Operating Temperature Range: -40°C To +75°C

OSP6AU Multi-Conductor - Category 6A Outside Plant Cable

Non-UL Temperature Rating:	75C
Bulk Cable Weight:	48 lbs/1000 ft.
Max. Recommended Pulling Tension:	40 lbs.
Min. Bend Radius/Minor Axis:	3 in.
Min. Bend/Installation:	3.750 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II):	Yes
IEEE Specification:	POE per IEEE 802.3af & POE+ per IEEE 802.3at-2009
Other Standards:	ISO/IEC 11801 ed 2 Amendment 2:2010 Class EA
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/15/2016
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6A - TIA 568.C.2
ANSI Specification:	ANSI/ICEA S-99-689 Broadband Outdoor Use, ANSI/ICEA standard S-116-732-2013 Category 6A
Other Specification:	ANSI/ICEA S-56-434 Outdoor Use

Applicable Patents:

Country
www.belden.com/p

Suitability

Suitability - Indoor:	No
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	Yes
Suitability - Hazardous Locations:	No
Sunlight Resistance:	Yes
Oil Resistance:	No
Non-halogenated:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	10GXS13
Non-Plenum Number:	10GXS12

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)
17.000

Maximum Capacitance Unbalance (pF/100 m):	45
---	----

Nominal Velocity of Propagation:

VP (%)
65.000

Maximum Delay:

Delay (ns/100 m)
537.000

Typical Delay Skew:

Delay Skew (ns/ft)
30.000

Max. Delay Skew:

OSP6AU Multi-Conductor - Category 6A Outside Plant Cable

Delay Skew (ns/100 m)

45.000

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

8.200

Max. Operating Voltage - UL:

Voltage

300 V RMS

Maximum DCR Unbalanced:

Description	DCR Unbalance @ 20°C (%)
Conductor-to-Conductor	3.000
Pair-to-Pair	7.500

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. PSNEXT (dB)	Min. PSACR (dB)	Min RL (dB)
1	2.100	72.3	70.2	20.000
4	3.800	63.3	59.5	23.000
8	5.300	58.8	53.4	24.500
10	5.900	57.3	51.4	25.000
16	7.500	54.2	46.8	25.000
20	8.400	52.8	44.4	25.000
25	9.400	51.3	42.0	24.300
31.25	10.500	49.9	39.4	23.600
62.5	15.000	45.4	30.4	21.500
100	19.100	42.3	23.2	20.100
200	27.600	37.8	10.2	18.000
250	31.100	36.3	5.3	17.300
300	34.300	35.1	0.9	16.800
350	37.200	34.1		16.300
400	40.100	33.3		15.900
450	42.700	32.5		15.500
500	45.300	31.8		15.200

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. PSACRF (dB)
1	100 ± 15	105 ± 10	64.8
4	100 ± 15	100 ± 15	52.8
8	100 ± 15	100 ± 15	46.7
10	100 ± 15	100 ± 15	44.8
16	100 ± 15	100 ± 15	40.7
20	100 ± 15	100 ± 15	38.8
25	100 ± 15	100 ± 15	36.8
31.25	100 ± 15	100 ± 10	34.9
62.5	100 ± 15	100 ± 10	28.9
100	100 ± 15	100 ± 10	24.8
200	100 ± 22	100 ± 10	18.8
250	100 ± 32	100 ± 10	16.8
300	100 ± 32	100 ± 10	14.3
350	100 ± 32	100 ± 10	13.9
400	100 ± 32	100 ± 10	12.8
450	100 ± 32	100 ± 10	11.7
500	100 ± 32	100 ± 10	10.8

Premise Cable Electrical Table 4:

Frequency (MHz)	Min. PSANEXT (dB)	Min. PSAACRF (dB)	Min. TCL (dB)	Min. ELTCTL (dB)
1.000	67.000	67.000	40.000	35.000
4.000	67.000	66.200	40.000	33.000
8.000	67.000	60.100	40.000	16.900
10.000	67.000	58.200	40.000	15.000
16.000	67.000	54.100	38.000	10.900
20.000	67.000	52.200	37.000	9.000
25.000	67.000	50.200	36.000	7.000
31.250	67.000	48.300	35.100	5.500
62.500	65.600	42.300	32.000	
100.000	62.500	38.200	30.000	
200.000	59.600	32.200	27.000	

OSP6AU Multi-Conductor - Category 6A Outside Plant Cable

250.000	58.000	30.200	26.000	
300.000	55.300	28.700	25.200	
350.000	54.300	27.300	24.600	
400.000	53.500	26.200	24.000	
450.000	54.300	25.100	23.500	
500.000	52.000	24.200	23.000	

Notes (Overall)

Notes: Third party channel verified to TIA/EIA-568-C.2, Category 6A. Print Includes Descending Footage / Meter Markings. -40C Cold Bend Compliance Per UL1581. Reference T8-6-T8-6 for Burial. Water Penetration per GR 421-CORE para. 4.3.5.1. and ANSI/ICEA S-107-704 Para. 8.2.1.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
OSP6AU 0101000	1,000 FT	53.000 LB	BLACK		CAT6A 4PR U/UTP OSP REEL

Revision Number: 1 Revision Date: 07-31-2017

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).