


## 2137A Multi-Conductor - Category 5e Indoor/Outdoor OSP/CM-LS LSZH Cable



For more Information  
please call

1-800-Belden1



### General Description:

CAT5e (100 MHz), 4 Pair, U/UTP-Unshielded, Indoor/Outdoor OSP/CM-LS, Premise Horizontal Cable, 24 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Gel-Filled, UV-Resistant Flame Retardant Haloarrest® LSZH Jacket

### Usage (Overall)

**Suitable Applications:** OSP, CM-LS, Low Smoke, Indoor/Outdoor, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Outside Plant

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	24	Solid	BC - Bare Copper

**Total Number of Conductors:** 8

#### Insulation

**Insulation Material:**

Insulation Material
PO - Polyolefin

#### Outer Shield

**Outer Shield Material:**

Outer Shield Material
Unshielded

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material
FR Polyolefin

**Outer Jacket Diameter:**

Nom. Dia. (in.)
0.251

#### Pair

**Pair Color Code Chart:**

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Mechanical Characteristics (Overall)

<b>Storage Temperature Range:</b>	-40°C To +75°C
<b>Installation Temperature Range:</b>	-20°C To +60°C
<b>Operating Temperature Range:</b>	-20°C To +60°C
<b>Bulk Cable Weight:</b>	21 lbs/1000 ft.
<b>Max. Recommended Pulling Tension:</b>	35 lbs.
<b>Min. Bend Radius/Minor Axis:</b>	2.500 in.
<b>Min. Bend/Installation:</b>	2.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

**NEC/(UL) Specification:** CM-LS

## 2137A Multi-Conductor - Category 5e Indoor/Outdoor OSP/CM-LS LSZH Cable

CEC/C(UL) Specification:	CM-LS
AWM Specification:	UL Style 444 (300 V 75°C)
EU Directive 2011/65/EU (ROHS II):	Yes
IEEE Specification:	POE per IEEE 802.3af
EU CE Mark:	No - External
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 5e - TIA 568.C.2, ISO/IEC 11801:2011 Amendment 2.2 Class D
ANSI Specification:	ANSI/ICEA S-56-434 Outdoor Use, ANSI/ICEA S-99-689 Broadband Outdoor Use
Other Specification:	NEMA WC-63.1 Category 5e

### Flame Test

UL Flame Test:	UL1581 Vertical Flame and FT-1 Flame Test
C(UL) Flame Test:	FT1
CSA Flame Test:	FT1
Other Flame Test:	Smoke Density: IEC 1034, Combustion Gasses: IEC 754-2

### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	Yes
Sunlight Resistance:	Yes

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

#### Nom. Mutual Capacitance:

Capacitance (pF/ft)  
15

Maximum Capacitance Unbalance (pF/100 m): 330

#### Nominal Velocity of Propagation:

VP (%)  
68

#### Maximum Delay:

Delay (ns/100 m)  
510 @ 100MHz

#### Max. Delay Skew:

Delay Skew (ns/100 m)  
45

#### Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)  
9.38

#### Max. Operating Voltage - UL:

Voltage  
300 V RMS

#### Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)  
3

### Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

## 2137A Multi-Conductor - Category 5e Indoor/Outdoor OSP/CM-LS LSZH Cable

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)
1	2.000	65.3	62.3	63.0	60.3	20.000
4	4.100	56.3	53.3	51.0	49.2	23.000
8	5.800	51.8	48.8	46.0	43.0	24.500
10	6.500	50.3	47.3	43.0	40.8	25.000
16	8.200	47.3	44.3	39.0	36.0	25.000
20	9.300	45.8	42.8	36.5	33.5	25.000
25	10.400	44.3	41.3	33.9	30.9	24.300
31.25	11.700	42.9	39.9	31.0	28.2	23.600
62.5	17.000	38.4	35.4	22.0	19.0	21.500
100	22.000	35.3	32.3	14.0	10.3	20.100
155	28.100	32.5	29.5	4.4	1.4	18.800
200	32.000	30.8	27.8			18.000

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.8	60.8
4	100 ± 15	100 ± 15	51.7	48.7
8	100 ± 15	100 ± 15	45.7	42.7
10	100 ± 15	100 ± 15	43.8	40.8
16	100 ± 15	100 ± 15	39.7	36.7
20	100 ± 15	100 ± 15	37.7	34.7
25	100 ± 15	100 ± 15	35.8	32.8
31.25	100 ± 15	100 ± 15	33.9	30.9
62.5	100 ± 15	100 ± 15	27.8	24.9
100	100 ± 15	100 ± 15	23.8	20.8
155	100 ± 25	100 ± 15	20.0	17.0
200	100 ± 25	100 ± 15	17.8	14.8

### Notes (Overall)

**Notes:** Print Includes Descending Footage / Meter Markings. -20C Cold bend per UL 1581, Water Penetration per GR 421-CORE para. 4.3.5.1, and ANSI/ICEA S-107-704 Para. 8.2.1

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
2137A 0101000	1,000 FT	39.000 LB	BLACK		CAT5E 4PR U/UTP OSP-CM REEL

Revision Number: 0    Revision Date: 07-31-2017

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.