

2139A Multi-Conductor - Category 5e Indoor/Outdoor OSP/CM-LS LSZH 25pr Corrugated Shield Cable



For more Information
please call

1-800-Belden1



General Description:

CAT5e (100 MHz), 25 Pair, U/UTP-Unshielded, Indoor/Outdoor OSP/CM-LS, Premise Backbone Cable, 24 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Gel-Filled, Polyolefin Inner Jacket, Corrugated Aluminum Tape, Ripcord, UV-Resistant Flame Retardant Haloarrest® LSZH Outer Jacket

Usage (Overall)

Suitable Applications: Indoor/Outdoor, Premise Backbone Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, OSP, Outside Plant

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
25	24	Solid	BC - Bare Copper

Total Number of Conductors: 50

Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

Inner Jacket

Inner Jacket Material:

Inner Jacket Trade Name	Inner Jacket Material	Nom Wall (in.)	Nom. Dia. (in.)
Polyolefin	Medium Density Polyethylene	0.040	0.510

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (in.)
Polyolefin	Flame Retardant Polyethylene	0.060

Outer Jacket Diameter:

Nom. Dia. (in.)
0.730

Outer Jacket Ripcord: Yes

Outer Jacket over Armor (y/n): Yes

Outer Jacket over Armor

Outer Jacket Material over Armor (y/n): Yes

Outer Jacket Material Over Armor:

OJ Over Armor Trade Name	OJ Over Armor Material	Nom. Wall (in.)	Dia. (in.)
Corrugated Aluminum Tape	Aluminum	0.008	0.610

Outer Jacket Wall Thickness Over Armor: 0.060

Armor

Armor Type: Corrugated Tape

Armor Material: Aluminum

Armor Thickness: 0.008

Diameter over Armor: 0.610

Overall Cable

Overall Cabling Fillers: 2 x Polyolefin ROD fillers - inner layer.

Overall Nominal Diameter: 0.730 in.

2139A Multi-Conductor - Category 5e Indoor/Outdoor OSP/CM-LS LSZH 25pr Corrugated Shield Cable

Pair

Pair Color Code Chart:

Number	Color
1	Black & Blue
2	Black & Orange
3	Black & Green
4	Black & Brown
5	Black & Gray
6	Yellow & Blue
7	Yellow & Orange
8	Yellow & Green
9	Yellow & Brown
10	Yellow & Gray
11	Purple & Blue
12	Purple & Orange
13	Purple & Green
14	Purple & Brown
15	Purple & Gray
16	White & Orange
17	White & Green
18	White & Brown
19	White & Gray
20	Red & Blue
21	Red & Orange
22	Red & Green
23	Red & Brown
24	Red & Gray
25	White & Blue

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +75°C
Installation Temperature Range:	-20°C To +60°C
Operating Temperature Range:	-20°C To +60°C
UL Temperature Rating:	60C
Installation Temperature Rating:	60C
Bulk Cable Weight:	332 lbs/1000 ft.
Max. Recommended Pulling Tension:	165 lbs.
Min. Bend Radius/Minor Axis:	7.500 in.
Min. Bend/Installation:	14.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM-LS
CEC/C(UL) Specification:	CM-LS
EU Directive 2011/65/EU (ROHS II):	Yes
IEEE Specification:	POE per IEEE 802.3af
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 5e - TIA 568.C.2, ISO/IEC 11801:2011 Amendment 2.2 Class D
ANSI Specification:	ANSI/ICEA S-56-434 Outdoor Use, ANSI/ICEA S-99-689 Broadband Outdoor Use
Other Specification:	NEMA WC-63.1 Category 5e

Flame Test

UL Flame Test:	UL1581 Vertical Tray
----------------	----------------------

2139A Multi-Conductor - Category 5e Indoor/Outdoor OSP/CM-LS LSZH 25pr Corrugated Shield Cable

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	Yes
Suitability - Hazardous Locations:	No
Sunlight Resistance:	Yes
Non-halogenated:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)
14.000

Maximum Capacitance Unbalance (pF/100 m): 330

Nominal Velocity of Propagation:

VP (%)
68.000

Maximum Delay:

Delay (ns/100 m)
538 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)
45

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
9.38

Max. Operating Voltage - UL:

Voltage
300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)
5

Electrical Characteristics-Premise (Overall)

Premise Cable Electricals:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. PSNEXT (dB)	Min. SRL (dB)	Fitted Imp. (Ohms)
.772	1.800	64	19.4	100 ± 15%
1	2.000	62.3	20	100 ± 15%
4	4.100	53.3	23.0	100 ± 15%
8	5.800	48.8	24.5	100 ± 15%
10	6.500	47.3	25	100 ± 15%
16	8.200	44.3	25	100 ± 15%
20	9.300	42.8	25	100 ± 15%
25	10.400	41.3	24.3	100 ± 15%
31.25	11.700	39.9	23.6	100 ± 15%
62.5	17.000	35.4	21.5	100 ± 15%
155	28.100	29.4	18.8	100 ± 15%
100	22.000	32.3	20.1	100 ± 15%
200	32.400	27.8	18.0	100 ± 15%

Premise Cable Electrical Table 2:

Freq. (MHz)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
0.772	66	63.0
1	63.8	60.8
4	51.8	48.8
8	45.7	42.7
10	43.8	40.8
16	39.7	36.7
20	37.8	34.8
25	35.8	32.8

ENGLISH MEASUREMENT VERSION

2139A Multi-Conductor - Category 5e Indoor/Outdoor OSP/CM-LS LSZH 25pr Corrugated Shield Cable

31.25	33.9	30.9
62.5	27.9	24.9
100	23.8	20.8
155	20.0	17.0
200	17.8	14.8

Notes (Overall)

Notes: Third party verified to TIA/EIA-568-C.2, Category 5e, Print Includes Descending Footage / Meter Markings, -20C Cold bend per UL 1581, Water Penetration per GR 421-CORE para. 4.3.5.1, and ANSI/ICEA S-107-704 Para. 8.2.1

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
2139A 0101000	1,000 FT	350.000 LB	BLACK		CAT5E 25PR CAT OSP-CM REEL

Revision Number: 0 Revision Date: 07-31-2017

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.