

# Generic Paint Specification 2101

## Tredgrip on aluminium

**Description:** - This spec is to achieve a non-slip elastomeric coating on aluminium. It is water based, and is designed for on-site application.

**Application:** - Typical applications include boat decks, stairs and steps, access ramps, etc. Not suitable for areas where vehicles will be parked e.g. driveways and car parks.

**Products:**

1. Envirothane 8054 universal primer
2. Tredgrip

**Process:**

Details	Indicative Coverage
1. Clean thoroughly and abrade	
2. Prime with Envirothane 8054	8m <sup>2</sup> /Litre
3. 1 <sup>st</sup> coat Tredgrip	6ms/Litre
4. 2 <sup>nd</sup> Coat – Tredgrip	6m <sup>2</sup> /Litre

**Notes:**

1. Surface must be sound, dry, and free of all loose material, laitance, old coatings, dust, and other surface contaminants.
2. Adhesion of the final system is highly dependent on surface preparation. The ultimate method of abrading aluminium is to whip-blast with a non-metallic abrasive. At the very least the surface should be prepared by hand tool abrasion.
3. Typical application methods include brush, soft broom or long nap roller.

Notes:

1. This specification should be read in conjunction with all relevant Product Data Sheets and Material Safety Data Sheets.
2. This specification is offered free of charge as a guide. Any warranty will be strictly limited to supply of replacement materials. No further liability for failure or associated costs will be borne by A&I Coatings.
3. Being a generic spec, there may be situations or conditions not considered that could influence the performance or appearance of the finished product. If you have any query in this regard, you should request a Site Unique Specification.
4. Product usage rates and film build required will vary from project to project in reflection of the varying wear factors and substrate conditions.
5. In addition, Area Specific Instruction Sheets are available on request.