

Generic Paint Specification 2102

Tredgrip on timber

Description: - This spec is to achieve a non-slip elastomeric coating on timber. It is water based, and is designed for on-site application.

Application: - Typical applications include patios and decks, stairs and steps, access ramps, etc. Not suitable for areas where vehicles or heavy objects will be parked e.g. ramps for vehicles and mezzanine storage facilities.

Products:

1. Envirothane 8054 Primer
2. Tredgrip

Process:

Details	Indicative Coverage
1. Clean thoroughly	
2. Prime with Envirothane 8054	8m ² /Litre
3. 1 st coat Tredgrip	6ms/Litre
4. 2 nd Coat – Tredgrip	6m ² /Litre

Notes:

1. Surface must be sound, dry, and free of all loose material, laitance, old coatings, dust, and other surface contaminants.
2. This system is recommended for open-grained timbers, such as pine and cedar, as well as processed products such as treated pine, MDF and particle board. This system is NOT recommended for external hardwoods due to high levels of tannins and dense grain, restricting penetration of the waterborne coating.
3. Typical application methods include brush, soft broom or long nap roller.

Notes:

1. This specification should be read in conjunction with all relevant Product Data Sheets and Material Safety Data Sheets.
2. This specification is offered free of charge as a guide. Any warranty will be strictly limited to supply of replacement materials. No further liability for failure or associated costs will be borne by A&I Coatings.
3. Being a generic spec, there may be situations or conditions not considered that could influence the performance or appearance of the finished product. If you have any query in this regard, you should request a Site Unique Specification.
4. Product usage rates and film build required will vary from project to project in reflection of the varying wear factors and substrate conditions.
5. In addition, Area Specific Instruction Sheets are available on request.