

Generic Paint Specification 2105

Tredgrip on compressed fibre cement

Description: - This spec is to achieve a non-slip elastomeric coating on CFC. It is water based, and is designed for on-site application.

Application: - Typical applications include decks and patios, stairs and steps, walkways and footpaths, access ramps, pool surrounds, sporting facilities etc. Not suitable for areas where vehicles will be parked e.g. driveways and carparks.

Products:

1. Enviroset 2100 two pack water borne epoxy primer
2. Tredgrip

Process:

Details	Indicative Coverage
1. CFC should be primed with Enviroset 2100	6m ² /Litre
2. 1 st coat Tredgrip	6m ² /Litre
3. 2 nd Coat – Tredgrip	6m ² /Litre

Notes:

1. Surface must be sound, dry, and free of all loose material, laitance, old coatings, dust, and other surface contaminants.
2. Adhesion of Tredgrip should be checked and verified prior to starting the project, to ensure adequate adhesion is achieved.
3. Where a joint sealing system is going to be used, the entire system should first be tested for compatibility.
4. Typical application methods include brush, soft broom or long nap roller.

Notes:

1. This specification should be read in conjunction with all relevant Product Data Sheets and Material Safety Data Sheets.
2. This specification is offered free of charge as a guide. Any warranty will be strictly limited to supply of replacement materials. No further liability for failure or associated costs will be borne by A&I Coatings.
3. Being a generic spec, there may be situations or conditions not considered that could influence the performance or appearance of the finished product. If you have any query in this regard, you should request a Site Unique Specification.
4. Product usage rates and film build required will vary from project to project in reflection of the varying wear factors and substrate conditions.
5. In addition, Area Specific Instruction Sheets are available on request.