

# UV CURED WOOD SEALER

## VITRECURE 30 CLEAR SEALER



### ► Product Description:

VITRECURE 30 is the sealer for the Vitrecure UV System for the coating of timber slats, veneered panelling, flooring etc. It is available in clear and pigmented forms. It sands readily and provides an excellent base for Vitrecure 32 or 33 top coats.

### ► Technical

Colour: Clear or White

Finish: Satin

Solids: 100%

Rec. Film

Thickness: 2 at 15 - 25g/m<sup>2</sup> (15 - 20 microns)

### Information:

Flexibility: Adequate for any normal substrate movement.

Viscosity: (23 °C) 120 - 200 seconds DIN 4 Cup.

It is available in extra high, high, medium, or low viscosity.

### ► Application:

Method of Application: Roller coater.

Lamps: VC30 Clear requires 2MpHg lamps at 80w/cm  
VC30 White requires 1Ga lamp at 120w/cm and 2MpHg lamps at 80w/cm.

Cure Speed: 10-15 m/min

### ► Health & Safety:

Users must first read the Material Safety Data Sheet for VC30.

### DISCLAIMER:

Since the use and application of this product is beyond our control, we cannot be held responsible for product field performance. The information represented above is the result of our considerable experience with this product but is not to be construed as a performance warranty.

For additional information, please phone our  
Customer Service Centre 1800 819 585