



CMT100 - 0.75 METRE



MixKing - 1.34 METRE

TRAILER MOUNTED CONCRETE MIXERS

Everyday thousands of Cart-Away's concrete trailers help contractors, municipalities and homeowners save both time and money on ready-mixed concrete delivery. Since the mid 1980's Cart-Away has been manufacturing rotating drum mix trailers that replicate what happens at a typical ready mix operation. These trailers allow for concrete to be transported to job sites without compromising quality. Chemicals and fibre can be added and as the drum rotates, will be dispersed throughout the concrete. There is no need for remixing at the job site.

These portable concrete mixers allow you to be in control of how much concrete you need and when it will be delivered. No more short load fees or additional labour costs due to waiting for ready mix trucks.

FEATURES

- Single-axis rotating drum
- Precision drum parts
- Ross hydraulic motor with cross-port relief valve
- Honda Engine
- GearSaver™ Knob for increased gearbox life
- TandemFlex™ fenders withstand dents



BUILT TO LAST BY



TRAILER MOUNTED CONCRETE MIXERS

SPECIFICATIONS

CMT100 - 0.75 CUBIC METRE

- Hydraulic surge brakes (electric brake option)
- Tires are Load Range C, ST 205/75 DT 15 rated at 1,820 pounds per tire
- Empty weight 1107kg
- 7000 GVWR or 0.75 cubic metre capacity
- Precision rotating drum
- 11 hp Honda Engine
- Auburn Heavy Duty Gearbox
- Ross hydraulic motor w/crossport relief
- 4 wheel free-backing brakes
- Vari-height adjustable tongue
- Standard 2" ball or optional pintel
- GearSaver Knob for gearbox safety
- Dimensions 1.6m by 1.7m by 2.4m
- Tandem 1588 kg axles
- D.O.T. Approved lights
- Uni-body hydraulic valve
- Tubular A36 structural steel frame
- Plastic Tandemflex fenders

MIXKING - 1.34 CUBIC METRE

- Hydraulic surge brakes (electric brake option)
- Load range D ST225/75 15" radial tires with a 2540# rating
- Empty weight 1225kg
- 10,000 GVWR or 1.34 cubic metre capacity
- Precision rotating drum
- 13 hp Honda Engine
- Auburn Heavy Duty Gearbox
- Ross hydraulic motor w/crossport relief
- 4 wheel free-backing brakes
- Vari-height adjustable tongue
- Standard pintel ring
- GearSaver Knob for gearbox safety
- Dimensions 4.6m x 1.7m x 3.3m
- Tandem 5200lb. axles
- D.O.T. Approved lights
- Uni-body hydraulic valve
- Tubular A36 structural steel frame
- Plastic Tandemflex fenders

OPTIONS



DISCHARGE CHUTE allows you to move concrete from the mouth of the drum into forms or holes with ease. The non-stick plastic chute can be moved between trailers that have the mounting assembly.



VINYL DRUM COVER provides an extra level of protection from spillage while in transit.



PORTAWASH SYSTEM is an on-board water system that provides water when none is available at the jobsite, enabling easy clean-up. It comes with a 23 gallon tank; 25' perma-coil hose; 3.5 gal per minute pump with 45 P.S.I.

DELCO
EQUIPMENT

2648 Kepler Road, Elginburg, ON K0H 1M0
Tel: 613-545-1950 Toll Free: 1-877-715-2544
Email: sales@delcorequipment.com

DELCOREQUIPMENT.COM