



IQ Base Transmitter

## IQ Base™ Transmitter

The IQ Base Transmitter is a fast and reliable pager transmitter designed to work with all JTECH pagers. With UHF technology, your signal has a unique system ID which eliminates interference.

The IQ Base can manage up to 9999 pagers and supports all JTECH guest and staff pagers including: QuietCall®, SmartCall® IQ, StaffCall® IQ and GuestCall® IQ pagers.

### Additional Features

The IQ Base Transmitter is beautifully designed with an 8-line LED backlit interface and quick setup.

#### UHF Technology

Up to 2-mile range with unique ID to prevent signal interference.

#### Durable

Built with high-quality materials for maximum durability and industry leading performance.

#### Bright LED Display

Easy-to-read LED backlit digital display. Quick buttons make repeated communications a breeze.

#### Smart Alerts

Out-of-Range and Search ensures guest contact and minimizes pager loss.

#### Manager, Staff & Guest Pagers

Supports the full line of JTECH pagers.

#### Manager Button

Instantly call the manager to provide additional assistance as necessary.

Call today for more information



# IQ Base™

## Guest & Staff Paging Transmitter

### Specifications

|                              |  |
|------------------------------|--|
| <b>Display</b>               | <ul style="list-style-type: none"> <li>&gt; 2 x 3 inch 8 line display</li> <li>&gt; Blue LED backlit digital screen</li> <li>&gt; Water-resistant polyurethane</li> </ul>  |
| <b>Interfaces</b>            | <ul style="list-style-type: none"> <li>&gt; Serial: DB9- DCE (female) Connector</li> <li>&gt; Data Rates: 1200, 9600, 38400, 57600</li> <li>&gt; Characters: 8 Data Bits</li> <li>&gt; Stop Bits: 1</li> </ul>   |
| <b>Electrical</b>            | <ul style="list-style-type: none"> <li>&gt; Frequency range: 450 - 468 MHZ</li> <li>&gt; FCC Identifier: WDC-IQBASE-N</li> <li>&gt; IC Identifier: 7752A-IQBASE-N</li> <li>&gt; Channel Spacing: 12.5 KHz</li> <li>&gt; Speed / Baud Rate: 512/1200 bps</li> </ul> |
| <b>Power</b>                 | <ul style="list-style-type: none"> <li>&gt; DC 12V, 3.5A, SMPS</li> <li>&gt; RF Output (Watts): 2 Watts</li> <li>&gt; Format: POCSAG</li> </ul>  |
| <b>Long Range Technology</b> | <ul style="list-style-type: none"> <li>&gt; UHF Frequency</li> <li>&gt; Unique System ID eliminates interference</li> <li>&gt; Up to 2-mile range</li> </ul>   |

### Dimensions

|                            |                               |                           |
|----------------------------|-------------------------------|---------------------------|
| <b>IQ Base Transmitter</b> | Length: 9.37 inches (23.7 cm) | Width: 5.5 inches (14 cm) |
|                            | Height: 1.75 inches (4.3 cm)  | Weight: 1.6 lbs (0.72 k)  |

### Works With:



GuestCall® Pagers



QuietCall® & SmartCall



StaffCall IQ® Pagers



### JTECH, an HME Company

JTECH is the largest onsite paging company in the world and the leading provider of onsite messaging solutions for hospitality, healthcare, retail, church nurseries and other markets.

©2017 JTECH, an HME Company logo and product names are registered trademarks of HM Electronics, Inc. All rights reserved.



PS17-TXNEO-v1