



Restroom Attendant
Restroom Attendant
Transmitter & Pager

Restroom Attendant™ Maintenance Alert System

Unlike current time-based methods where restrooms are checked every hour, Restroom Attendant tracks traffic in and out of the restroom. Optimize time, save on supplies and have restrooms cleaned when it matters the most.

Our traffic-based restroom service pager is great for all public buildings, including: restaurants, schools, hospitals and convenience stores. If your establishment has peak hours of use, it makes sense to service your restroom only when you need to. Your business establishment is unique. That's why our restroom service pager is flexible. You determine the number of visits required before Restroom Attendant™ alerts your manager or staff.

Additional Features

Restroom Attendant helps you maintain a clean, well-serviced restroom. Finally, you can eliminate the guesswork and keep up the great service with ease.

Completely Programmable

Depending on the size of your restroom, you can program the number of visits required before sending an alert.

Low Profile

Easy to install, the discreet design will not interfere with your restroom décor.

User-Replaceable Batteries

Replace your own batteries to reduce downtime and cost.

Manager Pager Included

Comes with it's own pager or can be programmed to one of our Alpha-Numeric Pagers.

Low Battery Alert

Low battery notification provided via pager.

Flexible Installation

Can easily be modified depending on door orientation.

Call today for more information



Restroom Attendant Maintenance Alert System

Specifications

Frequency	<ul style="list-style-type: none"> > Frequency Range: 450-470 MHz > FCC Identifier: WDC-RESTTX > IC Identifier: 7752A-RESTTX > Channel Spacing: 12.5 KHz
Electrical	<ul style="list-style-type: none"> > Format: POCSAG > RF Output (Watts): 50 mWatts > Deviation: +/-4.5 KHz > Modulation Scheme: FSK
Alerts	<ul style="list-style-type: none"> > Maintenance alert sent to multiple pagers > Escalation page sent to manager > Programmable maintenance alerts based on number of visits
Battery	<ul style="list-style-type: none"> > AA size x 2 / 3.6V Lithium battery (4,800 mAh) > User replaceable > Est. 18-24 months > Low battery alert sent to pager
Smart Technology	<ul style="list-style-type: none"> > Magnetic door / infrared sensor > Customizable visit threshold > Visits based on door openings
Range	<ul style="list-style-type: none"> > Effective Range: Up to .25 miles > Unique System ID eliminates interference > Speed / Baud Rate: 512 / 1200

Staff Pager Options



StaffCall IQ®



Alpha-Numeric Pager



Rugged Pager

Dimensions

Restroom Attendant Transmitter	Length: 1.26 inches (3.2 cm)	Width: 2.08 inches (5.28 cm)
	Height: 3 inches (7.62 cm)	Weight: 0.25 lbs (0.11 k)
Rugged Belt Pager Charger	Length: 4.25 inches (10.79 cm)	Width: 4.25 inches (10.79 cm)
	Height: 0.8 inches (2.03 cm)	Weight: 0.30 lbs (0.17 k)



JTECH, an HME Company

JTECH is the largest onsite paging company in the world and the leading provider of onsite messaging solutions for hospitality, healthcare, retail, church nurseries and other markets.

©2017 JTECH, an HME Company logo and product names are registered trademarks of HM Electronics, Inc. All rights reserved.

PS17-TXNEO-v1

