



ServerCall Transmitter  
& Cancel Panel  
24 Button Panel

## ServerCall®

The ServerCall Transmitter and Cancel Panel helps your kitchen manage food pick up more effectively and profitably. With the ServerCall Transmitter empower your kitchen staff to instantly notify servers when food is ready for delivery while it's hot and fresh. Add the Cancel panel to allow servers to conveniently cancel the page when the food is picked up without interrupting the kitchen workflow.

The ServerCall Transmitter and Cancel Panel are available in 12, 24, 48 or 72 button panels. With features like One-Touch Paging and Auto-Recall, you can streamline kitchen traffic and notify servers when they're needed. The ServerCall Transmitter also has programmable "Duty Alerts" for quick reminders and communication.

### Additional Features

The ServerCall Transmitter supports up to 999 pagers and you can choose the type of pager that meets your needs.

#### UHF Technology

Up to 2-mile range with unique ID to prevent signal interference.

#### Auto-Recall

Automatically pages the server up to 3 times when food is ready for pick-up. The manager is automatically paged after the 3rd time to provide further assistance.

#### Multiple Pager and Transmitter Options

Mix and match pagers for the best solution to fit your budget and operation.

#### All-Page

Allows managers to quickly send a message to the entire staff for shift meetings, menu changes, etc.

#### Restaurant Tough

Engineered with durable plastic made to withstand the quick-service restaurant environment.

#### Manager Button

Instantly calls the manager to provide additional assistance as necessary.

Call today for more information



# ServerCall®

For the Kitchen

## Specifications

### Display

- > 12 / 24 / 48 / 72 Button Panel Options
- > Tri-color server lights for speed-of-service alerts
- > Dry erase panel with marker holder
- > Water-resistant polyurethane

### Interfaces

- > Serial: DB9- DCE (female) Connector
- > Data Rates: 1200, 9600, 38400, 57600
- > Telco: RJ11 4-pin connector to PBX

### Network

- > Interface: Ethernet 10Base-T, RJ45 connector
- > Protocols: TCP/IP, ARP, ICMP
- > Indicators (LED): Link & Activity
- > Management: SNMP, Telnet, Serial, Internal Web Server and Windows based utility for configuration

### Electrical

- > Frequency range: 450 - 468 MHZ
- > FCC Identifier: QBTLTK - SCT
- > IC Identifier: 5269A - LTKSCT
- > Channel Spacing: 12.5 KHZ
- > Speed / Baud Rate: 512/1200 bps

### Power

- > DC 12V, 3.5A, SMPS
- > RF Output (Watts): 2 Watts
- > Format: POCSAG

### Long Range Technology

- > UHF Frequency
- > Unique System ID eliminates interference
- > Up to 2-mile range

## Dimensions

### ServerCall Transmitter

Length: 8.26 inches (20.9 cm)    Width: 14.96 inches (37.9 cm)  
 Height: 5.9 inches (14.9 cm)    Weight: 4.28 lbs (1.9 kg)



JTECH, an HME Company

JTECH is the largest onsite paging company in the world and the leading provider of onsite messaging solutions for hospitality, healthcare, retail, church nurseries and other markets.

©2017 JTECH, an HME Company logo and product names are registered trademarks of HM Electronics, Inc. All rights reserved.

PS17-TXNEO-v1



## ServerCall Options



ServerCall Transmitter  
12 Button Panel



ServerCall Cancel Panel  
12 Button Panel

## Manager & Staff Pager Options



StaffCall IQ®



Alpha-Numeric Pager



Rugged Pager